

IMPRIMACION MULTI-USO ECOBARP AL AGUA



Product Description

Primer water based based on special maximum performance resins
Provides preparations with good adhesion and sealing effect on different surfaces



Technical Characteristics

Colour	White
Appearance	Matt
Touch-dry	30-60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 4-6 hours
Yield	8 - 10 m ² /l, coat, depending on conditions of surface
Thinner	Water
Storage	Excellent for up to 6 months, unopened, in original packaging, at normal temperature and humidity.. Store in places protected against frost.

Properties

- Antioxidant properties
- Easy to apply
- Good covering power.
- Enhances adherence of finishing coats
- Adherence on different substrates.
- Half aqueous composition
- Minimum odour
- Environmentally friendly

Applications

Suitable for protection and adherence on galvanised steel surfaces, cold rolled steel, aluminium, brass, copper and other light alloys, gypsum plaster, plaster and wood.

Method of Use

- Stir the contents of the pot well
- Apply in thin, even, well-spread coats
- A round brush and robot: as supplied in the container or slightly diluted with water.
- At airless spray gun, adjust viscosity with water.

Preparation of surfaces

- Clean and sand if necessary to eliminate dust, grease, oil, damp, old or deteriorated paint.
- Apply one or more coats until the substrate is covered

Recommendations before application

- Do not apply in temperatures below 5°C.

Other data

Packaging 0.375L, 0.75L, 4L and 15L

VOCS GR/L

59.6

Remarks

For toxicological standards, consult FICHA DE SEGURIDAD.
Clean utensils with water immediately after use.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 17-05-2016 This sheet replaces all previous versions.