

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 1

Compilation date: 14/11/2012

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** PROXL - 2K PREFILLED AEROSOL

**Product code:** CF4002K

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** PROXL

SECOND AVENUE

CHATHAM

KENT

ME4 5AU

ENGLAND

**Tel:** 01634 823900

**Fax:** 01634 813807

**Email:** sales@capellasolutionsgroup.com

**1.4. Emergency telephone number**

**Emergency tel:** 01634 823900

(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CHIP:** F+: R12; Xi: R36; -: R66; -: R67; Sens.: R42/43

**Most important adverse effects:** Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. May cause sensitisation by inhalation and skin contact.

**2.2. Label elements**

**Label elements under CHIP:**

**Hazard symbols:** Extremely flammable.

Irritant.



**Risk phrases:** R12: Extremely flammable.

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 2

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R42/43: May cause sensitisation by inhalation and skin contact.

**Safety phrases:** S24: Avoid contact with skin.

S37: Wear suitable gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S33: Take precautionary measures against static discharges.

S60: This material and its container must be disposed of as hazardous waste.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### DIMETHYL ETHER

EINECS	CAS	CHIP Classification	CLP Classification	Percent
204-065-8	115-10-6	F+: R12 Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	50-70%

##### ACETONE

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	---------	---------------------------------	---	--------

##### POLI(ESAMETILEN DIISOCIANATO) (A)

-	28182-81-2	Sens.: R43	-	1-10%
---	------------	------------	---	-------

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 3

ETHYL METHYL KETONE

201-159-0	78-93-3	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---------------------------------	--	-------

N-BUTYL ACETATE

204-658-1	123-86-4	-: R10; -: R66; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	--	--	-------

ISOPHORONE DIISOCYANATE, HOMOPOLYMER (A)

-	53880-05-0	Sens.: R43	-	1-10%
---	------------	------------	---	-------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	-: R10 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
-----------	----------	--	--------------------	-------

BUTAN-1-OL

200-751-6	71-36-3	-: R10; Xn: R22; Xi: R37/38; Xi: R41; -: R67	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	--	---	-------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	Xn: R65; -: R10; Xi: R37; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%
-----------	------------	-------------------------------------	---	-----

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 4

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 5

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**DIMETHYL ETHER**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m <sup>3</sup>	958 mg/m <sup>3</sup>	-	-

**ACETONE**

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

**ETHYL METHYL KETONE**

UK	600 mg/m <sup>3</sup>	899 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**N-BUTYL ACETATE**

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**2-METHOXY-1-METHYLETHYL ACETATE**

UK	274 mg/m <sup>3</sup>	548 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

**BUTAN-1-OL**

UK	-	154 mg/m <sup>3</sup>	-	-
----	---	-----------------------	---	---

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 6

**9.1. Information on basic physical and chemical properties**

**State:** Aerosol

**Colour:** Colourless

**Odour:** Characteristic odour

**Solubility in water:** Miscible

**Boiling point/range°C:** N/A

**Flammability limits %: lower:** 2.6

**Flash point°C:** -1

**Vapour pressure:** 5200 hPa

**VOC g/l:** 817.0

**Melting point/range°C:** Undetermined

**upper:** 18.6

**Autoflammability°C:** Not self igniting

**Relative density:** Not Determined

**9.2. Other information**

**Other information:** Not applicable.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Relevant effects for mixture:**

Effect	Route	Basis
--------	-------	-------

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 7

Irritation	OPT	Hazardous: calculated
Sensitisation	INH DRM	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** Not applicable.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This substance is not identified as a PBT substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1950

[cont...]

**SAFETY DATA SHEET**  
PROXL - 2K PREFILLED AEROSOL

Page: 8

**14.2. UN proper shipping name**

Shipping name: AEROSOLS

**14.3. Transport hazard class(es)**

Transport class: 2

**14.4. Packing group**

**14.5. Environmental hazards**

Environmentally hazardous: No

Marine pollutant: No

**14.6. Special precautions for user**

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and 3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

[cont...]



## SAFETY DATA SHEET

PROXL - 2K PREFILLED AEROSOL

Page: 9

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R12: Extremely flammable.

R22: Harmful if swallowed.

R36: Irritating to eyes.

R37/38: Irritating to respiratory system and skin.

R37: Irritating to respiratory system.

R41: Risk of serious damage to eyes.

R42/43: May cause sensitisation by inhalation and skin contact.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

