



J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA
Other means of identification:
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Barpimo, S.A.
San Fernando, 116
26300 Nájera - La Rioja - España
Phone: +34 941 410 000 - Fax: +34 941 410 111
fds@barpimo.com
www.barpimo.com
- 1.4 Emergency telephone number:** +34 941 410 000 (sólo disponible en horario de oficina)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
-  
- Hazard statements:**
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Substances that contribute to the classification**
Polyamide
UFI: 3NEF-W03Q-G00C-THVK
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 68410-23-1 EC: 614-452-7 Index: Non-applicable REACH: 01-2119972323-38-XXXX	Polyamide⁽¹⁾ Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317 - Danger	Self-classified 4,9 - <9,9 %
CAS: 7727-43-7 EC: 231-784-4 Index: Non-applicable REACH: 01-2119491274-35-XXXX	Barium Sulfate⁽²⁾ Regulation 1272/2008	Not classified 4,9 - <9,9 %
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	2-butoxyethanol⁽¹⁾ Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	ATP ATP15 0,9 - <2,4 %
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽²⁾ Regulation 1272/2008	Not classified <0,24 %
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	2-(2-butoxyethoxy)ethanol⁽²⁾ Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	ATP CLP00 <0,24 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 4: FIRST AID MEASURES (continued)

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and destroy using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)		
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	IOELV (8h)		0,5 mg/m ³
	IOELV (STEL)		
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	IOELV (8h)	20 ppm	98 mg/m ³
	IOELV (STEL)	50 ppm	246 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	IOELV (8h)	50 ppm	308 mg/m ³
	IOELV (STEL)		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	IOELV (8h)	10 ppm	67,5 mg/m ³
	IOELV (STEL)	15 ppm	101,2 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Polyamide CAS: 68410-23-1 EC: 614-452-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,9 mg/m ³	Non-applicable
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10 mg/m ³	10 mg/m ³
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	1091 mg/m ³	246 mg/m ³	98 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³

DNEL (General population):

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Polyamide CAS: 68410-23-1 EC: 614-452-7	Oral	Non-applicable	Non-applicable	0,56 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,56 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,97 mg/m ³	Non-applicable
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Non-applicable	Non-applicable	13000 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10 mg/m ³	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
	Inhalation	426 mg/m ³	147 mg/m ³	59 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
	Inhalation	Non-applicable	60,7 mg/m ³	40,5 mg/m ³	40,5 mg/m ³

PNEC:



Identification				
Polyamide CAS: 68410-23-1 EC: 614-452-7	STP	3,14 mg/L	Fresh water	0,004 mg/L
	Soil	82,18 mg/kg	Marine water	0 mg/L
	Intermittent	0,041 mg/L	Sediment (Fresh water)	411,01 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	41,1 mg/kg
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	STP	62,2 mg/L	Fresh water	0,115 mg/L
	Soil	207,7 mg/kg	Marine water	Non-applicable
	Intermittent	Non-applicable	Sediment (Fresh water)	600,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	STP	463 mg/L	Fresh water	8,8 mg/L
	Soil	2,33 mg/kg	Marine water	0,88 mg/L
	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L
	Soil	2,74 mg/kg	Marine water	1,9 mg/L
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	STP	200 mg/L	Fresh water	1,1 mg/L
	Soil	0,32 mg/kg	Marine water	0,11 mg/L
	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -



J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)


Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	1,1 % weight
V.O.C. density at 20 °C:	14,03 kg/m ³ (14,03 g/L)
Average carbon number:	6,29
Average molecular weight:	119,38 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	78,18 kg/m ³ (78,18 g/L)
EU limit for the product (Cat. A.J):	140 g/L (2010)
Components:	K0864 - 12,5 % v/v

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C: Liquid

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Appearance:	Viscous
Colour:	Characteristic
Odour:	Not available
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	101 °C
Vapour pressure at 20 °C:	2343 Pa
Vapour pressure at 50 °C:	12346,9 Pa (12,35 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1280 kg/m ³
Relative density at 20 °C:	1,28
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	6 - 10
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	204 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: propan-2-ol (3); 2-butoxyethanol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LD50 oral	1200 mg/kg	Rat
	LD50 dermal	3000 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (ATEi)	
Polyamide CAS: 68410-23-1 EC: 614-452-7	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	Non-applicable	
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

** Changes with regards to the previous version

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Acute toxicity:

Identification	Concentration	Species	Genus
Polyamide CAS: 68410-23-1 EC: 614-452-7	LC50 >1 - 10 (96 h)		Fish
	EC50 >1 - 10 (48 h)		Crustacean
	EC50 >1 - 10 (72 h)		Algae
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LC50 76000 mg/L (96 h)	Salmo gairdneri	Fish
	EC50 Non-applicable		
	EC50 Non-applicable		
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	LC50 1490 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 1815 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50 10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50 1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LC50 1300 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 2850 mg/L (24 h)	Daphnia magna	Crustacean
	EC50 53 mg/L (192 h)	Microcystis aeruginosa	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	NOEC 100 mg/L	Danio rerio	Fish
	NOEC Non-applicable		
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	NOEC 100 mg/L	Danio rerio	Fish
	NOEC 100 mg/L	Daphnia magna	Crustacean
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC Non-applicable		
	NOEC 0,5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BOD5	0,71 g O2/g	Concentration	100 mg/L
	COD	2,2 g O2/g	Period	14 days
	BOD5/COD	0,32	% Biodegradable	96 %
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BOD5	Non-applicable	Concentration	Non-applicable
	COD	0 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %

** Changes with regards to the previous version

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Degradability		Biodegradability	
	2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BOD5	0,25 g O2/g	Concentration
	COD	2,08 g O2/g	Period	28 days
	BOD5/COD	0,12	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BCF
	Pow Log	0.83
	Potential	Low
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BCF	0.46
	Pow Log	0.56
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Koc	8	Henry
	Conclusion	Very High	Dry soil	No
	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
- Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

- CONTINUED ON NEXT PAGE -

J6744 - IMPRIMACION EPOXI AL AGUA MATE BLANCA

SECTION 16: OTHER INFORMATION (continued)

Product contains PBT/vPvB substances (SECTION 2, SECTION 12):

- Removed substances
 - Octamethylcyclotetrasiloxane (556-67-2)
 - Decamethylcyclopentasiloxane (541-02-6)

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.
H318: Causes serious eye damage.
H412: Harmful to aquatic life with long lasting effects.
H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Classification procedure:

Skin Irrit. 2: Calculation method
Eye Dam. 1: Calculation method
Aquatic Chronic 3: Calculation method
Skin Sens. 1A: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -