


BESA-GLASS/HS
Solvent based clear coats

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** BESA-GLASS/HS
Solvent based clear coats
- Other means of identification:**
- UFI:** DM90-K0KF-800F-WHHY
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Varnish. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
BERNARDO ECENARRO, S.A.
Ugarte Industrialdea, 147
20720 Azkoitia - Gipuzkoa - Spain
Phone: +34 943 74 28 00 - Fax: +34 943 74 06 03
msds@besa.es
http://www.besa.es
- 1.4 Emergency telephone number:** +34 943742800 (8:00-13:00) (14:30-17:30)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning
- 
- Hazard statements:**
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT SE 3: H335 - May cause respiratory irritation.
- Precautionary statements:**
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
Contains Hydroxyphenyl benzotriazol derivative.

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 2: HAZARDS IDENTIFICATION (continued)

Substances that contribute to the classification

N-butyl acetate; Xylene; Hydrocarbons, C9, aromatics; Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate ¹ Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	ATP CLP00 10 - <25 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene ¹ Regulation 1272/2008 Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified 10 - <25 %
CAS: 128601-23-0 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics ¹ Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	Self-classified 2,5 - <5 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ² Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	ATP ATP01 0,5 - <1 %
CAS: Non-applicable EC: 400-830-7 Index: 607-176-00-3 REACH: 01-0000015075-76-XXXX	Hydroxyphenyl benzotriazol derivative ¹ Regulation 1272/2008 Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	ATP CLP00 0,5 - <1 %
CAS: 1065336-91-5 EC: 915-687-0 Index: Non-applicable REACH: 01-2119491304-40-XXXX	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ¹ Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361f; Skin Sens. 1A: H317 - Warning	Self-classified 0,2 - <0,25 %

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

² Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Xylene	Non-applicable	Non-applicable	
CAS: 1330-20-7	Non-applicable	Non-applicable	
EC: 215-535-7	11 mg/L (ATEi)		

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats**SECTION 4: FIRST AID MEASURES (continued)****By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits	
N-butyl acetate		IOELV (8h)	50 ppm / 241 mg/m ³
CAS: 123-86-4	EC: 204-658-1	IOELV (STEL)	150 ppm / 723 mg/m ³
Xylene		IOELV (8h)	50 ppm / 221 mg/m ³

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits	
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm / 442 mg/m ³
2-methoxy-1-methylethyl acetate		IOELV (8h)	50 ppm / 275 mg/m ³
CAS: 108-65-6	EC: 203-603-9	IOELV (STEL)	100 ppm / 550 mg/m ³

DNEL (Workers):

Identification			Short exposure		Long exposure	
			Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation		600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation		442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	150 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation		Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol derivative CAS: Non-applicable EC: 400-830-7	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	0,35 mg/m ³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Oral		Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal		Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	0,68 mg/m ³	Non-applicable

DNEL (General population):

Identification			Short exposure		Long exposure	
			Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral		2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal		6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation		300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral		Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal		Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation		260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	Oral		Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal		Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	32 mg/m ³	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral		Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal		Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	33 mg/m ³	33 mg/m ³
Hydroxyphenyl benzotriazol derivative CAS: Non-applicable EC: 400-830-7	Oral		Non-applicable	Non-applicable	0,025 mg/kg	Non-applicable
	Dermal		Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	0,085 mg/m ³	Non-applicable
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Oral		Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Dermal		Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
	Inhalation		Non-applicable	Non-applicable	0,17 mg/m ³	Non-applicable

PNEC:

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Identification				
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,064 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Hydroxyphenyl benzotriazol derivative CAS: Non-applicable EC: 400-830-7	STP	10 mg/L	Fresh water	0,002 mg/L
	Soil	2 mg/kg	Marine water	0 mg/L
	Intermittent	0,028 mg/L	Sediment (Fresh water)	3,37 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,337 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	STP	1 mg/L	Fresh water	0,002 mg/L
	Soil	0,21 mg/kg	Marine water	0 mg/L
	Intermittent	0,009 mg/L	Sediment (Fresh water)	1,05 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,11 mg/kg

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection


- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	49,98 % weight
V.O.C. density at 20 °C:	489,78 kg/m ³ (489,78 g/L)
Average carbon number:	7,07
Average molecular weight:	112,12 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	515 kg/m ³ (515 g/L)
EU limit for the product (Cat. B.E):	840 g/L (2010)
Components:	(Organic diluent); (Hardener solvent)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Colourless
Odour:	Solvent
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	133 °C
Vapour pressure at 20 °C:	947 Pa
Vapour pressure at 50 °C:	4891,99 Pa (4,89 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	970 - 990 kg/m ³
-------------------	-----------------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Relative density at 20 °C:	0,97 - 0,99
Dynamic viscosity at 20 °C:	124 - 106 cP
Kinematic viscosity at 20 °C:	117 mm ² /s
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	26 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Hydrocarbons, C9, aromatics (3); Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LD50 oral	3492 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	6193 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (ATEI)	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Hydroxyphenyl benzotriazol derivative CAS: Non-applicable EC: 400-830-7	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	LD50 oral	3230 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L	

Acute Toxicity Estimate (ATE mix):

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	4787,81 mg/kg (Calculation method)	0 %
Inhalation	47,88 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50 Non-applicable		
	EC50 Non-applicable		
	EC50 675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50 >10 - 100 mg/L (96 h)		Fish
	EC50 >10 - 100 mg/L (48 h)		Crustacean
	EC50 >10 - 100 mg/L (72 h)		Algae
Hydrocarbons, C9, aromatics CAS: 128601-23-0 EC: 918-668-5	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50 161 mg/L (96 h)	Pimephales promelas	Fish
	EC50 481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50 Non-applicable		

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
Hydroxyphenyl benzotriazol derivative CAS: Non-applicable EC: 400-830-7	LC50 >1 - 10 mg/L (96 h)		Fish
	EC50 >1 - 10 mg/L (48 h)		Crustacean
	EC50 >1 - 10 mg/L (72 h)		Algae
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	LC50 0,9 mg/L (96 h)	Danio rerio	Fish
	EC50 Non-applicable		
	EC50 1,7 mg/L (72 h)	Desmodesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC Non-applicable		
	NOEC 23,2 mg/L	Daphnia magna	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC 1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC 47,5 mg/L	Oryzias latipes	Fish
	NOEC 100 mg/L	Daphnia magna	Crustacean
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	NOEC Non-applicable		
	NOEC 1 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability	Biodegradability
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5 Non-applicable	Concentration Non-applicable
	COD Non-applicable	Period 5 days
	BOD5/COD Non-applicable	% Biodegradable 84 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5 Non-applicable	Concentration Non-applicable
	COD Non-applicable	Period 28 days
	BOD5/COD Non-applicable	% Biodegradable 88 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5 Non-applicable	Concentration 785 mg/L
	COD Non-applicable	Period 8 days
	BOD5/COD Non-applicable	% Biodegradable 100 %
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	BOD5 Non-applicable	Concentration 20 mg/L
	COD Non-applicable	Period 28 days
	BOD5/COD Non-applicable	% Biodegradable 38 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF 4
	Pow Log 1.78
	Potential Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF 9
	Pow Log 2.77
	Potential Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF 1
	Pow Log 0.43
	Potential Low

12.4 Mobility in soil:

Identification	Absorption/desorption	Volatility
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc Non-applicable	Henry Non-applicable
	Conclusion Non-applicable	Dry soil Non-applicable
	Surface tension 2,478E-2 N/m (25 °C)	Moist soil Non-applicable

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption			Volatility
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Koc	204400	Henry	0E+0 Pa·m ³ /mol
	Conclusion	Immobile	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 163, 367, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 14: TRANSPORT INFORMATION (continued)

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats**SECTION 15: REGULATORY INFORMATION (continued)****Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361f - Suspected of damaging fertility.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Aquatic Chronic 3: Calculation method

Skin Sens. 1A: Calculation method

STOT SE 3: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

STOT RE 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- CONTINUED ON NEXT PAGE -

BESA-GLASS/HS
Solvent based clear coats

SECTION 16: OTHER INFORMATION (continued)

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -