

Technical Datasheet

PISCICLOR

Product Code: 09180 Sports Installations



JUNO

DESCRIPTION

Chlorinated rubber paint for the protection and maintenance of cement and concrete pools and other sports installations. Provides a film with excellent resistance to immersion in water and chemical agents. Extraordinary resistance to weathering and discoloration.

USE: INTERIOR - EXTERIOR

Recommended for painting cement and concrete pools, masonry non-potable water tanks etc. Also recommended for sports facility flooring and parking spaces with light traffic.

PROPERTIES

- Blue color with guaranteed maximum coverage and stability
- Impeccable finish
- Waterproof
- Breathable
- Great elasticity
- Increased resistance when immersed in water
- Resistant to alkalis and surface salinity
- Maximum chemical and acid resistance
- Excellent resistance to atmospheric agents
- Easy application

Finish: Satin

Color: Blue

Viscosity: Min.90" S/FR1002

Density: 1,55 ± 0,05 g/cc S/FR1001

Drying: Al tacto 45 min

Min. Repaint time: 24 horas

Max. Repaint time: Ilimitado

Diluent: JUNO D-40 Thinner

Performance: 8 m²/L (per coat)

Volume Solids: 45 ± 2 % Theoretical - White

Flash Point: Inflammable (34 °C)

VOC Content: Maximum 450 g/l

09180 BLUE



Format: 4 L

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Technical Datasheet

PISCICLOR

Product Code: 09180 Sports Installations



SURFACE PREPARATION

CONCRETE & FIBRE CEMENT. Concrete must be properly set (min. 1 month). Polished concrete/cement surfaces must be prepared mechanically by blasting or milling to eliminate any efflorescence and achieve an open pore surface.

Both new and old surfaces should be washed with a solution of water and hydrochloric acid (10%) to open the pore. Rinse with clean water and let dry for at least 2 days. Treat salt peter and surface efflorescence before painting. Always check the humidity of the substrate before application. (max 4%).

On painted surfaces. Remove old loose and flaking paint that is in poor condition, and if necessary, repair the surface using suitable repair mortar/cement fix. Clean with water and bleach (30%). Rinse with water and let dry completely.

APPLICATION TIPS

Stir the paint ensuring total homogenization.

Apply on surfaces that are consistent, clean, free of efflorescence (salt peter) and molds.

The surfaces must be completely dry and not excessively overheated by the sun. Dilution of the paint depends on the porosity and state of the surface.

TEMPERATURE CONDITION. During the application and the curing process the temperature must be maintained above 10°C. The relative humidity should not exceed 80%. The surface temperature must be at least 3°C above the dew point. Avoid condensation. Do not apply with risk of rain or strong wind.

DILUENT. JUNO D-40 Thinner (Prod. Code 50.000). Dilute the first coat with 20-30% solvent. The second coat apply as is, or thinned with 5% solvent. To spray, dilute with 10-15% solvent.

APPLICATION METHOD. Brush, roller or spray equipment. Always apply in thin, well-stretched layers.

CLEANING. Immediately clean stains and work tools using **JUNO D-40 Thinner (Prod.Code 50.000)** or **JUNO D-45 Universal Thinner (Prod.Code 50.017)**.

OBSERVATIONS

It is recommended that the pools have an air chamber, to avoid the hydrostatic pressure in the ground.

The Pisciclor must be protected from moisture, condensation and water, at least during the first 24 hours after application.

For swimming pools, the characteristics of the terrain and location of the pool, the humidity insulation and conditions, as well as the correct application according to the application advice given, will influence greatly in the result and performance of this specialist coating.

The degree of gloss of the applied product may vary depending on the temperature and the absorption level of the painted surface. This effect can be minimized by applying additional coats of paint.

Once the pool is painted, wait 15 days before filling it to ensure full curing of the coating.

SAFETY AND ENVIRONMENT

Being a solvent-based product, it must be applied with good ventilation, and with the necessary protection measures.

Avoid sources of ignition. Minimize product waste by estimating the amount needed, taking into account the m², porosity and texture of the support.

Store the excess material in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over.

Close containers carefully and keep upright to avoid spills. Preserve the containers away from frost, high temperatures and direct sun exposure.

Store unused paint for later use as opposed to discarding it thus reducing environmental effects.

Do not eat, drink or smoke during the preparation and application of the product.

Surface preparation and application operations must be carried out with the corresponding safety measures.

For more information, consult the Safety Data Sheet.

In case of contact with eyes wash with clean and abundant water. Keep out of the reach of children.

Do not discharge into drains or the environment.

Dispose of at an authorized waste collection point. Consult your city council for the correct recycling method of both the container and leftover paint, according to local legislation and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet.

The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.