

CONVERTÓXIDO



Product Description

Rust converter based on special resins in aqueous medium and active substances which, when in contact with rust, form a black, stable chemical complex, creating a protective neutral layer that prevents rust from spreading.



Technical Characteristics

Colour	Ivory (on rusted surfaces, when dry turns black)
Appearance	Satin
Touch-dry	60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	6 hours (topcoat of another product, 24 hours).
Yield	9 - 12 m ² /l, coat, depending on conditions of surface
Thinner	Water
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

Properties

- Easy to apply
- Penetrates through all stratified rust layers
- Reacts, stabilises, sets and converts rust to a neutral protective layer preventing rust from spreading
- Forms a moisture-proof barrier
- Enhances adherence of finishing coats

Applications

- Suitable for rust removing mix on rusty iron and steel surfaces.
- Suitable for anti-corrosive treatment on iron and steel elements, pieces, structures, small repairs and patches on machinery, household appliances, vehicles.

Method of Use

- Stir the contents of the pot well
- Apply undiluted
- Application at: Round brush, airless spray gun and roller
- Pour the required quantity into another container and do not return unused product to the original pot to avoid the possibility of contamination

Preparation of surfaces

- Totally remove loose rust from the surface and dust, grease, oil, damp, old or deteriorated paint
- Apply 1 or 2 coats of Convertóxido and leaving repainting time between coats
- Apply minium synthetic undercoat or Anti-rust primer and finish with topcoats, Viking, Barpsint Alta Decoración, etc.

Recommendations before application

- Do not apply in temperatures below 10°C.

Other data

Packaging	0.5L, 1L and 25L
-----------	------------------

VOCS GR/L

0.011

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.
In outdoor use, as a water-based product, it is sensitive to the action of rain.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 07-11-2013 This sheet replaces all previous versions.