

TECHNICAL DATA SHEET

JUNORAL SOFT SHEEN – WHITE BASE

Code: 100004

AUGUST 2015

DESCRIPTION

Soft Sheen is a premium quality vinyl mid sheen emulsion formulated for interior use on walls and ceilings. It provides an attractive alternative to traditional Vinyl Silk and Vinyl Matt paints. Soft Sheen withstands normal levels of humidity and can be wiped clean. JUNO's Soft sheen reduces the need for excessive coats in any paint system, giving a faster turnaround time for painters.

USE: INTERIOR - EXTERIOR

Suitable for interior use on all normal interior wall and ceiling surfaces. Ideal for plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork etc.

PREPARATION

Use Brush, roller, conventional spray or airless spray. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. Stir thoroughly before using and occasionally when in use.

Read all label and Material Safety Data Sheet (MSDS) information prior to use. MSDS are available through our website.

- Apply on clean, dry and consolidated surfaces free from loose and flaking material. Prime bare surfaces with the appropriate JUNO Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

OBSERVATIONS

For all types of substrates:

In case of mould, fungus, algae or other parasite contaminations, take the following steps:

- Wash with 10% bleach and water solution.
- Rinse with water.
- Prime with Junosan Base Cleaner.
- Allow to dry thoroughly before painting.
- Use ANTI-MOULD products.

If saline efflorescence (saltpetre) is found:

- Brush and wash with 10% Hydrochloric Acid or 10% Zinc Sulphate solution.
- Rinse with water.
- Allow to dry thoroughly before painting.

These operations must be carried out under appropriate safety conditions.

Product must be stored protected from frost.

Dying: Use water-based Junoral Water or Universal Juno colorants, not exceeding 3% of colorant- Allow to fully dry before painting.

These operations must be carried out under appropriate safety conditions

Finish: Soft sheen

Color: Colors from Ral and NCS, Coltec, and other Charts

Viscosity: Min 80 Poises

Density: 1,26 ± 0.05 S/FR1007

**Drying time: 1-2 hours* to the touch
Repaint minimum 3-4 hours*.**

**Depending on surface humidity*

Diluent: Water

Performance: 12-14m2 / L/ coat

Health & Safety: Aqueous-phase paint product, exempt from labelling

VOC's content: Maximum 30g/l.

APPLICATION PROCEDURE

SUBSTRATE	PREPARATION	APPLICATION
		INTERIOR
Concrete, cement or mortar based on NEW hydraulic binders.	Cleaning Efflorescence removal	* 1 Coat of diluted Hidrocril * 2 Coats of Soft Sheen diluted with 10% water
Non-pulverous old paints	Cleaning and/or washing	* 2 Coats of Soft Sheen diluted with 10% water
Pulverous paints	Cleaning. Fix	* 1 Coat of Hidrocril diluted. * 2 Coats of Soft Sheen diluted with 10% water
Old paint in poor condition.	Remove.	* Same as new surfaces
Plaster, gypsum	Cleaning. Fix if necessary	* 1 Coat of Hidrocril diluted. * 2 Coats of Soft Sheen diluted with 10% water
Projected plasters	Given the problems occasionally associated with projected plaster painting, we recommend sealing the surfaces using AQUA-SELL, Code: 21203	

The information contained in this data sheet may vary and must be updated. Please visit www.juno.es or consult with your nearest JUNO representative who will provide you with the most recent date sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

TECHNICAL DATA SHEET

JUNORAL SOFT SHEEN - WHITE BASE

Code: 100004

APPLICATION RECOMMENDATIONS

Surface to be painted should be clean, dry and free from all forms of contamination. Remove all loose and flaking paint. Previously painted walls should be thoroughly washed down and then rinsed with clean water and allowed to dry.

Seal surfaces that remain powdery after thorough preparation with JUNO Hidrocril Sealer Undercoat. Where necessary, rub down and then wipe down with a damp, lint free cloth, to avoid dust. Avoid the inhalation of dust.

Stir the paint well before application to homogenize the paint and the color.

Follow the recommended application temperature and the drying times between coats (20°C, relative humidity 65%).

The thickness of application, temperature and humidity may affect drying times.

Buy only the necessary quantity required, taking into account the m², porosity and support texture.

Store the remaining product in a dry and well-ventilated place. Work with the appropriate ventilation and respect the safety precautions norms indicated in the safety data sheet of the product.

CLEANING

Wash stains as soon as possible with a clean lint free cloth and clean soapy water. Rinse and allow to dry.

Full paint properties do not develop for a minimum of 7 to 10 days after application (depending on drying conditions). The paint should not be washed before this time has elapsed.

Clean tools after use (brushes, rollers, pencils, machines etc.) and let them dry before storing.

Consult your town council about the appropriate recycling method for the container, waste and excess paint, in accordance with the existing legislation and environmental protection principles.

SHIPPING



Packaging: 4/10/15 liters
Shipping Weight:
Units per pallet: 150/33/33



Freight Classification:
 Paint or paint related material



Transport Information
 No restriction for transport (ADR/RID, IMDG, IATA)



The information contained in this data sheet may vary and must be updated. Please visit www.juno.es or consult with your nearest JUNO representative who will provide you with the most recent date sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.