

TOPCOATS

Size 500ml

Codes: GW500 - GLOSS WHITE: SB500 - SATIN BLACK: GB500 - GLOSS BLACK: MB500 - MATT BLACK

Products Characteristics

- Fast drying product with good spray characteristics
- · Suitable for internal and external use
- · Weather resistant, light proof and UV resistant
- · Scratch and impact resistant
- · Excellent surface hardness and good elasticity
- · Can be mechanically polished

Physical and chemical data

| Product Type | Nitro Combi | |
|---|---|--|
| Coverage | 1.56 - 2.19m² per 500ml | |
| Drying times | Dust Free 5 - 10minutes Touch Dry 10 - 20 minutes Overcoat able after 2 hours | |
| The drying time depends on temperature, humidity and the thickness of the applied coat. | | |

Surface Preparation

- · Prior to applying the topcoat, apply a suitable primer.
- The surface must be free from all contamination including rust, grease and moisture.
- Before use, carefully read and note the warning text on the label

Environmentally sound

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

