Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: SELLADOR INVISIBLE AL SILOXANO - Código - 68104

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Water repeller

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A. Barrio Sakoni, 10

48950 ERANDIO - Vizcaya - España

Phone.: +34 944 670 062 - Fax: +34 944 675 832

laboratorio@juno.es www.juno.es

1.4 Emergency telephone number: +34 944 670 062 (8:00 -15:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Asp. Tox. 1: Aspiration hazard, Category 1, H304

Flam. Liq. 3: Flammable liquids, Category 3, H226

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Flam. Liq. 3: H226 - Flammable liquid and vapour STOT SE 3: H336 - May cause drowsiness or dizziness

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish

P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking

EUH208: Contains Trimethoxy(methyl)silane. May produce an allergic reaction

Substances that contribute to the classification

Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (CAS: 64742-48-9)

2.3 Other hazards:

Product contains PBT/vPvB substances: Octamethylcyclotetrasiloxane

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 1/12



According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Mixture composed of additives in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration	
CAS:	64742-48-9	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7□¹□ ATP ATP01				
EC: Index: REACH:	265-150-3 549-327-00-6 01-2119486659-16- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	(! > (\$)(\$)	90 - <100 %	
CAS:	1185-55-3	Trimethoxy(methyl)	silane□¹□	Self-classified		
Index: Non-a REACH: 01-21	214-685-0 Non-applicable 01-2119517436-40- XXXX	Regulation 1272/2008	Flam. Liq. 2: H225; Skin Sens. 1: H317 - Danger	(1)	0,1 - <1 %	
CAS:	556-67-2	Octamethylcyclotetr	asiloxane□¹□	ATP CLP00		
EC: Index: REACH:	209-136-7 014-018-00-1 01-2119529238-36- XXXX	1-2119529238-36- Regulation 1272/2008	Aquatic Chronic 4: H413; Repr. 2: H361f - Warning	&	0,1 - <1 %	
CAS:	67-56-1	Methanol □²□		ATP CLP00		
EC: Index: REACH:	200-659-6 603-001-00-X 01-2119433307-44- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger		<0,1 %	

[□]¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 2/12

 $[\]square^2\square$ Substance with a Union workplace exposure limit

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 5: FIREFIGHTING MEASURES (continued)

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers ($CO\square$). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 3/12



According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 7: HANDLING AND STORAGE (continued)

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

	Identification		Environmental limits		
Methanol		IOELV (8h)	200 ppm	260 mg/m ³	
CAS: 67-56-1	EC: 200-659-6	IOELV (STEL)			

DNEL (Workers):

		Chart			
		Snort 6	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-48-9	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
EC: 265-150-3	Inhalation	Non-applicable	Non-applicable	1500 mg/m ³	Non-applicable
Trimethoxy(methyl)silane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1185-55-3	Dermal	Non-applicable	Non-applicable	6,6 mg/kg	Non-applicable
EC: 214-685-0	Inhalation	Non-applicable	Non-applicable	47 mg/m ³	Non-applicable
Octamethylcyclotetrasiloxane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 556-67-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 209-136-7	Inhalation	Non-applicable	Non-applicable	73 mg/m ³	14,6 mg/m ³
Methanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-56-1	Dermal	40 mg/kg	Non-applicable	40 mg/kg	Non-applicable
EC: 200-659-6	Inhalation	260 mg/m ³	260 mg/m ³	260 mg/m ³	260 mg/m ³

DNEL (General population):

		exposure	Long e	exposure
	Systemic	Local	Systemic	Local
Oral	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
Inhalation	Non-applicable	Non-applicable	900 mg/m ³	Non-applicable
Oral	Non-applicable	Non-applicable	0,42 mg/kg	Non-applicable
Dermal	132 mg/kg	Non-applicable	2,9 mg/kg	Non-applicable
Inhalation	353 mg/m ³	Non-applicable	10 mg/m ³	Non-applicable
Oral	3,7 mg/kg	Non-applicable	3,7 mg/kg	Non-applicable
Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Inhalation	13 mg/m ³	13 mg/m ³	13 mg/m ³	2,6 mg/m ³
Oral	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
Dermal	8 mg/kg	Non-applicable	8 mg/kg	Non-applicable
Inhalation	50 mg/m ³	50 mg/m ³	50 mg/m ³	50 mg/m ³
	Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation Oral Dermal Inhalation	Systemic Oral Non-applicable Dermal Non-applicable Inhalation Non-applicable Oral Non-applicable Dermal 132 mg/kg Inhalation 353 mg/m³ Oral 3,7 mg/kg Dermal Non-applicable Inhalation 13 mg/m³ Oral 8 mg/kg Dermal 8 mg/kg	Oral Non-applicable Non-applicable Dermal Non-applicable Non-applicable Inhalation Non-applicable Non-applicable Oral Non-applicable Non-applicable Dermal 132 mg/kg Non-applicable Inhalation 353 mg/m³ Non-applicable Oral 3,7 mg/kg Non-applicable Dermal Non-applicable Non-applicable Inhalation 13 mg/m³ 13 mg/m³ Oral 8 mg/kg Non-applicable Dermal 8 mg/kg Non-applicable Dermal 8 mg/kg Non-applicable	Systemic Local Systemic Oral Non-applicable Non-applicable 300 mg/kg Dermal Non-applicable Non-applicable 300 mg/kg Inhalation Non-applicable Non-applicable 900 mg/m³ Oral Non-applicable Non-applicable 0,42 mg/kg Dermal 132 mg/kg Non-applicable 2,9 mg/kg Inhalation 353 mg/m³ Non-applicable 10 mg/m³ Oral 3,7 mg/kg Non-applicable 3,7 mg/kg Dermal Non-applicable Non-applicable Non-applicable Inhalation 13 mg/m³ 13 mg/m³ 13 mg/m³ Oral 8 mg/kg Non-applicable 8 mg/kg Dermal 8 mg/kg Non-applicable 8 mg/kg

PNEC:



According to 1907/2006/EC (REACH), 2015/830/EU









SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Octamethylcyclotetrasiloxane	STP	10 mg/L	Fresh water	0,00044 mg/L
CAS: 556-67-2	Soil	0,15 mg/kg	Marine water	0,000044 mg/L
EC: 209-136-7	Intermittent	Non-applicable	Sediment (Fresh water)	0,59 mg/kg
	Oral	1,7 g/kg	Sediment (Marine water)	0,059 mg/kg
Methanol	STP	100 mg/L	Fresh water	154 mg/L
CAS: 67-56-1	Soil	23,5 mg/kg	Marine water	15,4 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	570,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CAT III	EN 149:2001+A1:2009 EN 405:2001+A1:2009	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

[&]quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CATIII	EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE
Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 5/12



According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 92,5 % weight

V.O.C. density at 20 °C: 701,97 kg/m³ (701,97 g/L)

Average carbon number: 8,95

Average molecular weight: 130,3 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 701,97 kg/m³ (701,97 g/L)

EU limit for the product (Cat. A.H): 750 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Characteristic

Odour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 148 °C Vapour pressure at 20 °C: 538 Pa

Vapour pressure at 50 °C: 3019,33 Pa (3,02 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Solubility in water at 20 °C:

Density at 20 °C: 758,9 kg/m³ 0,759 Relative density at 20 °C: Dynamic viscosity at 20 °C: 0,83 cP Kinematic viscosity at 20 °C: 1,09 cSt Kinematic viscosity at 40 °C: <20,5 cSt Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility properties: Soluble in organic solvents

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 6/12

Non-applicable *



According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature: Non-applicable *
Melting point/freezing point: Non-applicable *
Explosive properties: Non-applicable *
Oxidising properties: Non-applicable *

Flammability:

Flash Point: 24 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 200 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 7/12

^{*}Not relevant due to the nature of the product, not providing information property of its hazards.

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







Page 8/12

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Ac	Acute toxicity	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	LD50 oral	15000 mg/kg	Rat
CAS: 64742-48-9	LD50 dermal	3160 mg/kg	Rabbit
EC: 265-150-3	LC50 inhalation	Non-applicable	
Methanol	LD50 oral	100 mg/kg	Rat
CAS: 67-56-1	LD50 dermal	300 mg/kg	Rabbit
EC: 200-659-6	LC50 inhalation	3 mg/L (4 h)	Rat

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral >2000 mg/kg (Calculation method)		Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable



According to 1907/2006/EC (REACH), 2015/830/EU









SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Naphtha (petroleum), hydrotreated heavy, $<$ 0.1 % EC 200-753-7	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
CAS: 64742-48-9	EC50 1000 mg/L (96 h)		Daphnia magna	Crustacean
EC: 265-150-3	EC50	Non-applicable		
Octamethylcyclotetrasiloxane	LC50	500 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 556-67-2		Non-applicable		
EC: 209-136-7	EC50	Non-applicable		
Methanol	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 67-56-1	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
EC: 200-659-6	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 64742-48-9	COD	Non-applicable	Period	28 days
EC: 265-150-3	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
Methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1.42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential		
Octamethylcyclotetrasiloxane		12400		
CAS: 556-67-2		4.45		
EC: 209-136-7		Very High		
Methanol	BCF	3		
CAS: 67-56-1	Pow Log	-0.77		
EC: 200-659-6	Potential	Low		

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7	Кос	100	Henry	Non-applicable
CAS: 64742-48-9	Conclusion	High	Dry soil	Non-applicable
EC: 265-150-3	Surface tension	Non-applicable	Moist soil	Non-applicable
Octamethylcyclotetrasiloxane	Koc	Non-applicable	Henry	Non-applicable
CAS: 556-67-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 209-136-7	Surface tension	1,819E-2 N/m (25 °C)	Moist soil	Non-applicable
Methanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-659-6	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Octamethylcyclotetrasiloxane

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 9/12

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



14.1	UN number:	UN1263
14.2	UN proper shipping name:	PAINT
14.3	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
14.5	Environmental hazards:	No

14.5 Environmental hazards:14.6 Special precautions for user

Special regulations: 163, 367, 650

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



14.1	UN number:	UN1263
14.2	UN proper shipping name:	PAINT
14.3	Transport hazard class(es)	: 3
	Labels:	3
14.4	Packing group:	III

14.5 Environmental hazards:14.6 Special precautions for user

Special precautions for user Special regulations: 163, 223, 367, 955

EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **14.7 Transport in bulk according** Non-applicable

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2019:

- CONTINUED ON NEXT PAGE -

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 10/12

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 14: TRANSPORT INFORMATION (continued)



14.1UN number:UN126314.2UN proper shipping name:PAINT14.3Transport hazard class(es):3

Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Octamethylcyclotetrasiloxane

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

Date of compilation: 19/02/2013 Revised: 05/02/2019 Version: 12 (Replaced 11) Page 11/12

Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU

SELLADOR INVISIBLE AL SILOXANO - Código - 68104







SECTION 15: REGULATORY INFORMATION (continued)

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness

H304: May be fatal if swallowed and enters airways

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

Aquatic Chronic 4: H413 - May cause long lasting harmful effects to aquatic life

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour Repr. 2: H361f - Suspected of damaging fertility.

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT SE 1: H370 - Causes damage to organs

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

STOT SE 3: Calculation method

Asp. Tox. 1: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -