

Page 1/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

1.1 Product ide	ntifier	
Trade name: <u>M</u>	OTIP® CLE	EAR VARNISH 500 ML
No further relev Sector of Use SU21 Consum SU22 Professi Product catego Process catego PROC7 Indust PROC11 Non	entified uses of pant information er uses: Privation onal uses: Pu ry PC9a Coory ry trial spraying industrial spraying	ate households / general public / consumers ublic domain (administration, education, entertainment, services, craftsmen) atings and paints, thinners, paint removers
1.3 Details of th Manufacturer/S MOTIP DUPLI Wolfraamweg 2 NL- 8471 XC W The Netherland Tel: +31 (0)56 Fax: +31 (0)56 e-mail: msds@1	Supplier: B.V. Volvega s 1 694400 1 694411	f the safety data sheet .com
Further inform 1.4 Emergency +31 (0)561-694	telephone nu	
UK: NPIS Natio	onal Poisons I	Information Centre Tel: +44 0344 892 0111
SECTION 2	• Hazards i	dentification
		stance or mixture
		Regulation (EC) No 1272/2008
flame	?	
Aerosol 1	Н222-Н2	229 Extremely flammable aerosol. Pressurised container: May burst if heated.
	osion	
Corre		
Eye Dam. 1	H318	Causes serious eye damage.

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

STOT SE 3	(Contd. of <i>H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.</i>	pag
Aquatic Ch	ronic 3 H412 Harmful to aquatic life with long lasting effects.	
	<i>ccording to Regulation (EC) No 1272/2008</i> t is classified and labelled according to the CLP regulation.	
GHS02	GHS05 GHS07	
Signal word	1 Danger	
	ermining components of labelling:	
butan-1-ol Hydrocarbo	ons, C9, aromatics	
xylene	ns, c ² , aronancs	
~	ons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Hazard stat		
H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
Н335-Н336	May cause respiratory irritation. May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effects.	
Precaution	ary statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smol	kin
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P260	Do not breathe spray.	
P410+P412	2 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of contents / container in accordance with regional regulations.	
Additional	information:	
Buildup of e	explosive mixtures possible without sufficient ventilation.	
2.3 Other h	azards	
	PBT and vPvB assessment	
PBT: Not a		
vPvB: Not a	ıpplicable.	
SECTIO	N 3: Composition/information on ingredients	

Dangerous components:

*

· Dangerous components.		
CAS: 115-10-6	dimethyl ether	50-<75%
EINECS: 204-065-8	🚯 Flam. Gas 1A, H220	
Index number: 603-019-00-8	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119472128-37		

(Contd. on page 3) GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

EC number: 918-668-5	Hydrocarbons, C9, aromatics	10-<12
Reg.nr.: 01-2119455851-35	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 	_
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	<i>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%</i> <i>n-hexane</i>	5-<10
	 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 	_
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol ♦ Flam. Liq. 3, H226 ♦ Eye Dam. 1, H318 ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	5-<109
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H332 Aquatic Chronic 3, H412	<2.5%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

	(Contd. of page 3)
Keep away from ignition sources.	
· 6.2 Environmental precautions:	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
· 6.3 Methods and material for containment and cleaning up:	
Use neutralising agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· 6.4 Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm Sk

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· Ingredients with biological limit values:

xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

(Contd. on page 5)

GB

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

GB

Trade name: MOTIP® CLEAR VARNISH 500 ML

• Additional information: The lists valid during the making were used as basis.	(Contd. of page 4)
•	
· 8.2 Exposure controls	
• Personal protective equipment: • General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	
Do not inhale gases / fumes / aerosols.	
Avoid contact with the skin.	
Avoid contact with the eyes and skin.	
Avoid contact with the eyes.	
· Respiratory protection:	
In case of brief exposure or low pollution use respiratory filter device. In case of longer exposure use self-contained respiratory protective device.	intensive or
Filter A2/P3	
• Protection of hands:	
Trolection of humas.	
Protective gloves	
· Material of gloves	
Butyl rubber, BR	
The selection of the suitable gloves does not only depend on the material, but also on further	r marks of quality
and varies from manufacturer to manufacturer.	J 1 J
· Penetration time of glove material	
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:	
Acetone: 480 min	
Butyl acetate: 60 min	
Ethyl acetate: 170 min	
Xylene: 42 min	
Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As	
measure, we recommend that users and responsible persons for work safety assume solvent to	
of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistant	nce length in
particular cases.	
· Eye protection:	
Tightly sealed goggles	

SECTION 9: Physical and chemical properties

*

• 9.1 Information on basic physical at • General Information	nd chemical properties	
· Appearance:		
Form:	Aerosol	
Colour:	Colourless	
· Odour:	Solvent-like	
• Odour threshold:	Not determined.	
· pH-value:	Not determined.	
• Change in condition Melting point/freezing point:	Undetermined.	
		(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

	(Contd. of page
Initial boiling point and boiling range	e: Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
Decomposition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	26.2 Vol %
Vapour pressure at 20 $\cdot C$ (68 $\cdot F$):	4000 hPa (3000.2 mm Hg)
Density at 20 °C (68 °F):	0.8 g/cm ³ (6.7 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	88.1 %
VOC (EC)	
	661.9 g/l
VOC-EU%	88.14 %
Solids content:	11.7 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

*

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

·11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

		(Contd. of page 6)
xylene		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	29000 mg/m3 (rat)
71-36-3 bu	tan-1-ol	
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50/4 h	17000 mg/m3 (rat)
100-41-4 е	thylbenzene	2
Oral	LD50	3500 mg/kg (rat)
· Primary ir		
· Skin corro		on
	n irritation.	
	e damage/ir	
	ious eye dai	
		nsitisation Based on available data, the classification criteria are not met.
		al information:
		genity, mutagenicity and toxicity for reproduction)
		ty Based on available data, the classification criteria are not met.
		l on available data, the classification criteria are not met.
		Based on available data, the classification criteria are not met.
· STOT-sing		
May cause	respiratory	irritation. May cause drowsiness or dizziness.
STOT-repe	eated exposi	ure Based on available data, the classification criteria are not met.
Aspiration	hazard Bas	eed on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

2

· Aquatic toxicity:

115-10-6 dimethyl ether

EC50/96 h 155 mg/l (algae)

LC50/48 h >4000 mg/l (daphnia magna)

LC50 / 96 h >4000 mg/l (fish)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h 30-100 mg/l (algae)

LC50/96 h 11.4 mg/l (fish)

xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50/96 h 13.5 mg/l (fish)

71-36-3 butan-1-ol

LC50/96 h 1376 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

· Remark: Harmful to fish

• Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

2

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a maximum capacity of 1 titre Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear

- GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

	(Contd. of page
Segregation Code	of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre.
	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to A	Annex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.

(Contd. on page 10)

GB

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.02.2021

Version number 113

Revision: 17.12.2019

Trade name: MOTIP® CLEAR VARNISH 500 ML

	(Contd. of page 9)
H304 May be fatal if swallowed and enters airways.	
H312 Harmful in contact with skin.	
H315 Causes skin irritation.	
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H373 May cause damage to organs through prolonged or repeated exposure.	
H411 Toxic to aquatic life with long lasting effects.	
H412 Harmful to aquatic life with long lasting effects.	
11412 Harmjui to aquatic tije with long tasting effects.	
• Department issuing SDS: R&D legislation and regulatory advisor	
• Contact: msds@nl.motipdupli.com	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Re	gulations Concerning the
International Transport of Dangerous Goods by Rail)	0 0
ICAO: International Civil Aviation Organisation	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreem	ent Concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
• * Data compared to the previous version altered.	
	GB