

MOTIP Hollow Section Wax 1 I

Ord.-no.: 000034

Technical Information



Protect hollow spaces in the bodywork of your car against rust with MOTIP Hollow Section Wax. Hollow section wax is resistant to the weather and weak acids and bases and has an excellent rust prevention. Hollow section wax has good penetrating properties.

Quality & properties

- To be applied with an UBC spray-gun
- Excellent corrosion prevention
- Excellent adhesion
- Resistant to weather influences
- Resistant to weak acids and bases
- Good penetrating properties

Physical & chemical data

- Base: Wax
- Colourname: Transparent white
- Smell: characteristic
- Efficiency: 1,00 L – 6-7 m²
- Surfaces: Hollow spaces in vehicle bodywork
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Storage stability: 5 years
- Content: 1,00 L

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The can should have room temperature. Best processing temperature 15 to 25°C.
- Before use, shake the can. Working pressure 2,5 to 4 bar.
- Apply the wax generously in the hollow areas.
- After use, clean the spray-gun with white spirit

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 29, 2021 – This release replaces all eventually earlier issued versions.