

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** .4791 - NITROBARP 507 SEMIMATE 45
Other means of identification:
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Varnish. For industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Barpimo, S.A.
San Fernando, 116
26300 Nájera - La Rioja - España
Phone: +34 941 410 000 - Fax: +34 941 410 111
fds@barpimo.com
www.barpimo.com
- 1.4 Emergency telephone number:** +34 941 410 000 (sólo disponible en horario de oficina)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Eye Dam. 1: Serious eye damage, Category 1, H318
Flam. Liq. 2: Flammable liquids, Category 2, H225
Repr. 2: Reproductive toxicity, Category 2, H361d
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
STOT SE 2: Specific target organ toxicity — single exposure, Hazard Category 2, H371
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Eye Dam. 1: H318 - Causes serious eye damage.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 2: H371 - May cause damage to organs.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment

Substances that contribute to the classification

Toluene; 2-methylpropan-1-ol; methanol; Ethylbenzene

2.3 Other hazards:

Product contains PBT/vPvB substances: Octametilclotetrasiloxano, Decametilciclopentasiloxano

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Miscellaneous products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX	Toluene⁽¹⁾ Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	ATP CLP00 24 - <50 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	Xylene⁽¹⁾ Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	ATP CLP00 9,9 - <19,9 %
CAS: 110-19-0 EC: 203-745-1 Index: 607-026-00-7 REACH: 01-2119488971-22-XXXX	Isobutyl Acetate⁽²⁾ Regulation 1272/2008 Flam. Liq. 2: H225; EUH066 - Danger	ATP CLP00 9,9 - <19,9 %
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	2-methylpropan-1-ol⁽¹⁾ Regulation 1272/2008 Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	ATP CLP00 4,9 - <9,9 %
CAS: 123-42-2 EC: 204-626-7 Index: 603-016-00-1 REACH: 01-2119473975-21-XXXX	4-hydroxy-4-methylpentan-2-one⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	ATP CLP00 2,4 - <4,9 %
CAS: 67-56-1 EC: 200-659-6 Index: 603-001-00-X REACH: 01-2119433307-44-XXXX	methanol⁽¹⁾ Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	ATP CLP00 2,4 - <4,9 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: Non-applicable	Ethylbenzene⁽¹⁾ Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATPO 2,4 - <4,9 %
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	propan-2-ol⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	ATP CLP00 2,4 - <4,9 %
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	Butanone⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	ATP CLP00 0,9 - <2,4 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as possible with the SDS for the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Induce vomiting (ONLY IF PERSON IS CONSCIOUS!) and then ingest large quantities of liquid to dilute the toxin. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
		IOELV (8h)	IOELV (STEL)	IOELV (STEL)
Toluene CAS: 108-88-3 EC: 203-625-9		50 ppm		192 mg/m ³
			100 ppm	384 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7		50 ppm		221 mg/m ³
			100 ppm	442 mg/m ³
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1		50 ppm		241 mg/m ³
			150 ppm	723 mg/m ³
methanol CAS: 67-56-1 EC: 200-659-6		200 ppm		260 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4		100 ppm		442 mg/m ³
			200 ppm	884 mg/m ³
Butanone CAS: 78-93-3 EC: 201-159-0		200 ppm		600 mg/m ³
			300 ppm	900 mg/m ³

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
	Inhalation	384 mg/m ³	384 mg/m ³	192 mg/m ³	192 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	10 mg/kg	Non-applicable	10 mg/kg	Non-applicable
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	467 mg/kg	Non-applicable
	Inhalation	Non-applicable	240 mg/m ³	32,6 mg/m ³	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	20 mg/kg	Non-applicable	20 mg/kg	Non-applicable
	Inhalation	130 mg/m ³	130 mg/m ³	130 mg/m ³	130 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	Non-applicable	293 mg/m ³	77 mg/m ³	Non-applicable
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	500 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Toluene CAS: 108-88-3 EC: 203-625-9	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	Oral	5 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Dermal	5 mg/kg	Non-applicable	5 mg/kg	Non-applicable
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m ³
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5,8 mg/m ³	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Oral	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable
	Inhalation	26 mg/m ³	26 mg/m ³	26 mg/m ³	26 mg/m ³
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	15 mg/m ³	Non-applicable

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	89 mg/m ³	Non-applicable
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m ³	Non-applicable

PNEC:

Identification					
Toluene CAS: 108-88-3 EC: 203-625-9	STP	13,61 mg/L	Fresh water	0,68 mg/L	
	Soil	2,89 mg/kg	Marine water	0,68 mg/L	
	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg	
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	STP	200 mg/L	Fresh water	0,17 mg/L	
	Soil	0,075 mg/kg	Marine water	0,017 mg/L	
	Intermittent	0,34 mg/L	Sediment (Fresh water)	0,877 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,088 mg/kg	
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	STP	10 mg/L	Fresh water	0,4 mg/L	
	Soil	0,076 mg/kg	Marine water	0,04 mg/L	
	Intermittent	11 mg/L	Sediment (Fresh water)	1,56 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,156 mg/kg	
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	STP	100 mg/L	Fresh water	2 mg/L	
	Soil	0,3 mg/kg	Marine water	0,2 mg/L	
	Intermittent	1 mg/L	Sediment (Fresh water)	7,4 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,74 mg/kg	
methanol CAS: 67-56-1 EC: 200-659-6	STP	100 mg/L	Fresh water	20,8 mg/L	
	Soil	100 mg/kg	Marine water	2,08 mg/L	
	Intermittent	1540 mg/L	Sediment (Fresh water)	77 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	7,7 mg/kg	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L	
	Soil	2,68 mg/kg	Marine water	0,01 mg/L	
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg	
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg	
propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2251 mg/L	Fresh water	140,9 mg/L	
	Soil	28 mg/kg	Marine water	140,9 mg/L	
	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg	
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg	
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L	
	Soil	22,5 mg/kg	Marine water	55,8 mg/L	
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg	
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.



All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

- CONTINUED ON NEXT PAGE -



.4791 - NITROBARP 507 SEMIMATE 45

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer 's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer 's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	83,13 % weight
V.O.C. density at 20 °C:	768,95 kg/m ³ (768,95 g/L)
Average carbon number:	6,28
Average molecular weight:	92,91 g/mol

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	110 °C
Vapour pressure at 20 °C:	3993 Pa
Vapour pressure at 50 °C:	17364,08 Pa (17,36 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	925 kg/m ³
Relative density at 20 °C:	0,925
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	13 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	392 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Toluene (3); Polyethylene wax (3); Xylene (3); Ethylbenzene (2B); propan-2-ol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24,6 mg/L (4 h)	Rat
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	13630 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	LD50 oral	13413 mg/kg	Rat
	LD50 dermal	17400 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	
Toluene CAS: 108-88-3 EC: 203-625-9	LD50 oral	5580 mg/kg	Rat
	LD50 dermal	12124 mg/kg	Rat
	LC50 inhalation	28,1 mg/L (4 h)	Rat
methanol CAS: 67-56-1 EC: 200-659-6	LD50 oral	100 mg/kg	Rat
	LD50 dermal	300 mg/kg	Rabbit
	LC50 inhalation	3 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
** Changes with regards to the previous version CAS: 67-63-0 EC: 200-661-7	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72,6 mg/L (4 h)	Rat

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification	Concentration	Species	Genus
Toluene CAS: 108-88-3 EC: 203-625-9	LC50 5.5 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50 3.78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50 Non-applicable		
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	LC50 120 mg/L (48 h)	Leuciscus idus	Fish
	EC50 168 mg/L (24 h)	Daphnia magna	Crustacean
	EC50 80 mg/L (8 h)	Scenedesmus quadricauda	Algae
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	LC50 2030 mg/L (96 h)	Carassius auratus	Fish
	EC50 1439 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	LC50 420 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 9016 mg/L (24 h)	Daphnia magna	Crustacean
	EC50 530 mg/L (192 h)	Microcystis aeruginosa	Algae
methanol CAS: 67-56-1 EC: 200-659-6	LC50 15400 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 12000 mg/L (96 h)	Nitrocras spinipes	Crustacean
	EC50 530 mg/L (168 h)	Microcystis aeruginosa	Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50 42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50 75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 63 mg/L (3 h)	Chlorella vulgaris	Algae
propan-2-ol CAS: 67-63-0 EC: 200-661-7	LC50 9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50 13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Butanone CAS: 78-93-3 EC: 201-159-0	LC50 3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50 5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 4300 mg/L (168 h)	Scenedesmus quadricauda	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC 1.3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1.17 mg/L	Ceriodaphnia dubia	Crustacean
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	NOEC Non-applicable		
	NOEC 23.2 mg/L	Daphnia magna	Crustacean

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Concentration		Species	Genus
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	NOEC	Non-applicable		
	NOEC	20 mg/L	Daphnia magna	Crustacean
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	NOEC	Non-applicable		
	NOEC	100 mg/L	Daphnia magna	Crustacean
methanol CAS: 67-56-1 EC: 200-659-6	NOEC	15800 mg/L	Oryzias latipes	Fish
	NOEC	122 mg/L	Daphnia magna	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC	Non-applicable		
	NOEC	0.96 mg/L	Ceriodaphnia dubia	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Toluene CAS: 108-88-3 EC: 203-625-9	BOD5	2,5 g O2/g	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	20 days
	BOD5/COD	Non-applicable	% Biodegradable	81 %
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	BOD5	0,4 g O2/g	Concentration	100 mg/L
	COD	2,41 g O2/g	Period	14 days
	BOD5/COD	0,17	% Biodegradable	90 %
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
methanol CAS: 67-56-1 EC: 200-659-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	1,42 g O2/g	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	92 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BOD5	1,19 g O2/g	Concentration	100 mg/L
	COD	2,23 g O2/g	Period	14 days
	BOD5/COD	0,53	% Biodegradable	86 %

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Degradability		Biodegradability	
	Butanone CAS: 78-93-3 EC: 201-159-0	BOD5	2,03 g O2/g	Concentration
	COD	2,31 g O2/g	Period	20 days
	BOD5/COD	0,88	% Biodegradable	89 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Toluene CAS: 108-88-3 EC: 203-625-9	BCF
	Pow Log	2.73
	Potential	Moderate
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	BCF	10
	Pow Log	1.78
	Potential	Low
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	BCF	3
	Pow Log	0.76
	Potential	Low
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	BCF	0.5
	Pow Log	-0.34
	Potential	Low
methanol CAS: 67-56-1 EC: 200-659-6	BCF	3
	Pow Log	-0.77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BCF	3
	Pow Log	0.05
	Potential	Low
Butanone CAS: 78-93-3 EC: 201-159-0	BCF	3
	Pow Log	0.29
	Potential	Low

12.4 Mobility in soil:

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Identification	Absorption/desorption		Volatility	
Toluene CAS: 108-88-3 EC: 203-625-9	Koc	178	Henry	672,8 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Isobutyl Acetate CAS: 110-19-0 EC: 203-745-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,297E-2 N/m (25 °C)	Moist soil	Non-applicable
2-methylpropan-1-ol CAS: 78-83-1 EC: 201-148-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Non-applicable
4-hydroxy-4-methylpentan-2-one CAS: 123-42-2 EC: 204-626-7	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,963E-2 N/m (25 °C)	Moist soil	Non-applicable
methanol CAS: 67-56-1 EC: 200-659-6	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Koc	1.5	Henry	8,207E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Octametilclotetrasiloxano, Decametilclotpentasiloxano

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 163, 367, 640D, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Marine pollutant: No
14.6 Special precautions for user
 Special regulations: 367, 163
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
 Segregation group: Non-applicable
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: II
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: propan-2-ol (Product-type 1, 2, 4)
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

- CONTINUED ON NEXT PAGE -

.4791 - NITROBARP 507 SEMIMATE 45

SECTION 16: OTHER INFORMATION (continued)

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
Isobutyl Acetate (110-19-0)

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.
H318: Causes serious eye damage.
H336: May cause drowsiness or dizziness.
H373: May cause damage to organs through prolonged or repeated exposure.
H361d: Suspected of damaging the unborn child.
H371: May cause damage to organs.
H225: Highly flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 1: H370 - Causes damage to organs.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method
Eye Dam. 1: Calculation method
STOT SE 3: Calculation method
STOT RE 2: Calculation method
Repr. 2: Calculation method
STOT SE 2: Calculation method
Flam. Liq. 2: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -