

FONDIPOL 254 BLANCO

Product Description	White twin component solvent based pigmented polyurethane undercoat Alkyd nature
Properties	Quick drying High thixotropy that allows application without running on vertical surfaces and easy to spread on horizontal surfaces Quick and easy manual or machine sanding High filling power High solids, low solvent content, less effect on the environment Medium covering
Recommended use	Product to use for varnishing woodwork and indoor furniture

Technical Characteristics

	Norma	Value
Solids by weight (%)	UNE EN ISO 3251	75%+-2 10MIN 130°C
Viscosity (Ford cup 8)	UNE EN ISO 2431	75"+-10 F8 20°C
Density (Kg/L)	UNE EN ISO 2811-1	1.510+/-0.020

Mixing Characteristics

Hardener		K0312
Mix Proportion (% Volume)		50%
Viscosity of mix (Ford cup 4)	UNE EN ISO 2431	30" ± 5
Pot life mixture	UNE EN ISO 9514	2 to 3 hours at 20°C
Solvent		Reference: .9130

Application Characteristics

Application System	Aerographic and airless
Application on	DM previously sealed with priming insulation and steel plate
Recommended thickness of coat	150-180 gr/m ²
Number of coats	1-2
Touch-dry	20 a 40 minutes (depending on thickness and temperature)
Surface sanding	4 - 6 hours, depending on thickness applied and ambient conditions
Sanding	7 - 10 hours, depending on thickness applied and ambient conditions

Remarks re application process

- If you wish to seal the wood pores, you must sand the first undercoat before applying a second coat
- In the case of an increase in viscosity after the application, reduce with .9130
- If the ambient temperature is high, use .9020 to dilute
- On this undercoat you can apply any LACAPOL or NITROBARP top coat
- For application onto MDF, first it is necessary to apply an insulating sealant undercoat.

Remarks

- Shake contents of containers before use.
- Apply with good air renewal.
- Do not store opened or started containers.
- Maximum stability of hardener is less than 6 months at 20°C.
- For toxicological standards, consult FICHA DE SEGURIDAD.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 18-05-2017 This sheet replaces all previous versions.
