



FENICE S.p.A.

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY
+39 0445 424888 www.fenice.com

TECHNICAL DATA SHEET – Leather Care Div.

ADHESION PROMOTER

DESCRIPTION

Water-based adhesion promoter.

HOW TO USE

Adhesion Promoter is a soft polyurethane with extraordinary adhesion, high tenacity and low tack. **Adhesion Promoter** is employed as adhesion prebottoming coat before the application of **Touch Up Pigment** or **Pigment Base Coat** while reconstructing a pigmented finishing.

Directions: Apply by sponge in the difficult areas and then apply by spray, speeding up the drying process with a professional dryer. For exceptional results, mix **Adhesion Promoter** with 5% of **Eco-Crosslinker**. This mixture must be used within 8 hours.

PHYSICAL CONSTANTS	Standard Value	Test Method
Appearance	Whitish liquid	MDA 008
Density (g/cm ³)	1,01 ± 0,05	MDA 018
pH (1:10)	7,0 ± 1	MDA 004

STORAGE	Rev.
Non-dangerous product. Store between +5/40°C	07.2012

MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS

The product is guaranteed for its physical and quality characteristics 24 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.

All our information and suggestions are supplied on the basis of our present knowledge, and are subject to careful tests. However, we cannot accept responsibility for the use of the product, which must be verified and evaluated for its suitability or otherwise by the customer. Declared physical constants are monitored in production and guaranteed by FENICE S.p.A.