



FENICE S.p.A.

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY
+39 0445 424888 www.fenice.com

TECHNICAL DATA SHEET – Leather Care Div.

ECO CROSSLINKER

DESCRIPTION

Ecological and innovative crosslinker, to improve wet and dry rub resistances and adhesion of the finishing.

HOW TO USE

Eco Crosslinker is a water based, very powerful crosslinker. It is used in waterborne top coats, as well as with **Adhesion Promoter** to improve dry and wet rub resistance and adhesion. No particular precautions are needed in transportation.

Directions: **Eco Crosslinker** can be used in a ratio of 7-8% of the total weight of the final mix (**Top Coats, Adhesion Promoter, etc.**).

Important note: the addition should be made whilst stirring to ensure the complete homogenization of the crosslinker. Keep stirring for one minute after addition. Mixtures containing **Eco Crosslinker** must be used within 8 hours.

PHYSICAL CONSTANTS	Standard Value	Test Method
Appearance	Yellowish liquid	MDA 008
Active substances (%)	40	MDA 023

STORAGE	Rev.
Non-dangerous product. Store between +5/40°C	06.2013

MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS

The product is guaranteed for its physical and quality characteristics 6 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.

All our information and suggestions are supplied on the basis of our present knowledge, and are subject to careful tests. However, we cannot accept responsibility for the use of the product, which must be verified and evaluated for its suitability or otherwise by the customer. Declared physical constants are monitored in production and guaranteed by FENICE S.p.A.