PINTURA SEÑALIZACIÓN Y PÁRKINGS

Product Description	Paint road markings (traffic) based on special modified resins and highly colour fast pigments
	This product is excellent for road markings in towns, trunk roads, motorways, car parks, etc.
Carta de Colores	Carta de colores Pinturas para Suelos

Technical Characteristics

Colour	White, bright blue 108, royal yellow 105 and bright red 103
Appearance	Matt
Touch-dry	3-5 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 12 hours
Yield	9-12 m²/l, per coat, depending on the state and type of surface
Thinner	DILUYENTE SINTETICOS DE SECADO RAPIDO
Storage	Excellent up to 1 year in original container, under normal temperature and humidity conditions.

Properties

Easy to apply
Good covering power.
Filling power
Finish adherent, hard-wearing, with an ideal balance between hardness and elasticity
Resistant to abrasion

Applications

Suitable for road markings (traffic) on streets, roads, dual carriageways, motorways, car parks and garages and industrial buildings.
On asphalt, concrete surfaces, etc.

Method of Use

Stir the contents of the pot well
Apply in even coats and well ventilated
Application at: Round brush, spray gun, roller, special sign post machine and manual sign post machine

Preparation of surfaces

The surface must be clean, dry and consistent
Apply: 1 ó 2 coats

Other data

Packaging	4L, 15L
VOCS GR/L	394

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.

Apply with good air renewal.