

## BARPICOLOR 605 TIN



### Product Description

Liquid colorant concentrate

### Properties

Can be considered as a universal dye

Can be diluted in water, solvent or with hydroalcohol mixtures

Good resistance to bleeding and colour drag

Good stability when stored in tightly closed glass or plastic containers.

Good stability when stored in tightly closed glass or plastic containers.

Good stability when stored in tightly closed glass or plastic containers.

Very bright shades of colour

Varnish toner NC ,PU, SH and synthetics.

Good stability during storage.

Good stability when stored in tightly closed glass or plastic containers.

Good stability when stored in tightly closed glass or plastic containers.

Good stability when stored in tightly closed glass or plastic containers.

### Recommended use

Colour base for producing solvent based dyes in 645 quality and hydroalcoholic dyes and water-based ones for the VI tintometric system.

### Carta de Colores

[Linea de madera Aquabarp](#), [Linea Madera Tintes para madera](#)

### Certificados

[Certificado.de.Producto.Simbolo.de.Calidad.AIDIMA](#)



### Technical Characteristics

|                        | Norma | Value                 |
|------------------------|-------|-----------------------|
| Viscosity (Ford cup 4) |       | Fluid                 |
| Density (Kg/L)         |       | 1.020+-0.01 20°C      |
| Colour                 |       | Wide range of colours |
| Reference              |       | Depending on colour   |
| System                 |       | Universal             |
| Colouring power        |       | Medium - high         |
| Drying                 |       | Slow                  |

### Application Characteristics

|                    |                                                                                                |
|--------------------|------------------------------------------------------------------------------------------------|
| Application System | Aerographic, round brush, roller and rag                                                       |
| Touch-dry          | 1 a 2 min en tunel de aire caliente (Rodillo) minutes (depending on thickness and temperature) |
| Repainted          | 4-5 minutes                                                                                    |

### Remarks re application process

Spray-gun or manual application, diluted with water or solvent.

Application with a roller as supplied in the pot.

### Physical Chemical Resistance

|                             | Norma | Value                                                                                                                               |
|-----------------------------|-------|-------------------------------------------------------------------------------------------------------------------------------------|
| Solidity to varnishing over |       | Excellent resistance with nitro and PU varnishes.<br>Good resistance with UV (depending on concentration) and acid-based varnishes. |
|                             |       | Over-varnishing with polyester varnishes not advised.                                                                               |

**Remarks**

Shake contents of containers before use.  
For toxicological standards, consult FICHA DE SEGURIDAD.  
Do not store opened or started containers.  
Maximum stability of the product is less than 12 months at 20°C.

*This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 14-12-2010 This sheet replaces all previous versions.*