



FENICE S.p.A.

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY
+39 0445 424888 www.fenice.com

TECHNICAL DATA SHEET – Leather Care Div.

FM SLIP ADDITIVE

DESCRIPTION

Silky feel modifier.

HOW TO USE

FM Slip Additive is a feel modifier that allows one to obtain a silky and slightly wet feel. Moreover, when added to Top Coat it remarkably increases scuff and wet rub resistance.

Directions:

Use **FM Slip Additive** mixed with **Top Coat Gloss** or **Top Coat Matte** in a proportion of 5% according to the desired degree of slip required.

PHYSICAL CONSTANTS	Standard Value	Test Method
Appearance	Whitish fluid	MDA 008
Dry content (%)	35 ± 2	MDA 010/011
pH (1:10)	7.0 ± 1	MDA 004
Density (g/cm ³)	1.00 ± 0.05	MDA 018

STORAGE	Rev.
Non-dangerous product. Store between +5/40°C	10.2010

MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS

The product is guaranteed for its physical and quality characteristics 24 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.

All our information and suggestions are supplied on the basis of our present knowledge, and are subject to careful tests. However, we cannot accept responsibility for the use of the product, which must be verified and evaluated for its suitability or otherwise by the customer. Declared physical constants are monitored in production and guaranteed by FENICE S.p.A.