

BARNIZ HORMIGON IMPRESO

Product Description Solvent-based acrylic varnish, based on special resins to be applied on concrete, especially on printed concrete.



Technical Characteristics

Colour	Colourless
Appearance	Satin, semi-matt, depending on structure and absorption by the surface
Touch-dry	1 hour, depending on the absorption of the undercoat and ambient conditions
Repainting	After 2-3 hours
Yield	6-10 m ² /l, per coat, depending on the state and type of surface
Thinner	No need to dilute. Ready to use
Storage	Excellent up to 1 year in original container, under normal temperature and humidity conditions.

Properties

- Specially formulated for application on printed concrete
- Easy to apply
- Penetrating
- Filling power
- High sealing power
- Very permeable to the inner moisture of the surface
- Avoids efflorescence and nitre
- Resistant to the alkalinity of surfaces
- Can be walked on 24 hours after application

Applications

Recommended for application and protection of all kinds of concrete, specially printed concrete, providing refill, strengthening, and superficial hardness properties.
Suitable for all kind of metals, both indoors and outdoors

Method of Use

- Stir the contents of the pot well
- Apply in thin, even, well-spread coats
- Application at: Round brush, roller and spray gun
- Diluting is not recommended

Preparation of surfaces

The surface should be clean, dry and free from grease, nitre, flaking and must be consistent.
Concrete must be well setted.

Recommendations before application

- Residual humidity below 8%
- Do not apply in temperatures below 8°C.
- Relative ambient humidity below 80%
- Surface temperature higher than 8°C

Other data

Packaging 4L and 15L

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 11-05-2017 This sheet replaces all previous versions.