

2K EPOXY FLOOR PAINT J6745/6

Type of Product	Enamel topcoat based on epoxy resins reticulated with polyamide
Recommended use	Suitable for garages, workshops, wine cellars, industrial units, factories, car parks and concrete floors.
Properties	<p>Easy to apply</p> <p>Filling power</p> <p>Resistant to abrasion, to wear, mopping, oil spills, mineral oil, other chemical agents and dirt in general</p> <p>Eliminates the formation of dust on the floor, improves surface hardness, avoids erosion and wear and tea making the floor easier to clean and more decorative.</p> <p>Good properties in terms of hardness, elasticity and aesthetic appearance.</p>

Characteristics of supply

	Normativa	Specified
Colour	UNE EN ISO 3668	See colour chart
Gloss(geometry 60°)	UNE EN ISO 2813	Semi-gloss
Specific weight (Kg/L)	UNE EN ISO 2811-1	1.57 ± 0.05 (depending on colours)
Solids by weight in the mixture (%)	UNE EN ISO 3251	67% ± 3 (depending on colours)
Solids by volume in the mixture (%)	UNE 48090-82 (ISO 3233)	53% ± 3 (depending on colours)
Theoretical yield of the mixture (m ² /l)	UNE 48 282-94	7 - 9 m ² /l, coat, depending on conditions of surface
Conservation and Stability of the Container	UNE 48 083-92	9 months unopened, in original packaging. Store in a cool, dry place, away from frosts. Temperature range: 5-40°C

Application Instructions

Application equipment		Roller and round brush
Hardener		K0710
Mix proportion by volume		3/1
Mix shelf life		>8 hours
Application solvent	UNE EN ISO 9514	Reference: .9734

Drying / Polymerisation

Air drying (20°C-60% R.H.)	UNE 48301	(Touch) 5-6 hours
Repainting		12 - 24 hours

Remarks

See general conditions
 Apply the product when use and curing is at temperatures over 10°C. At the same time the paint temperature must also be over the limit value
 It is important to ventilate well during application on closed surfaces and subsequent polymerisation
 Do not store opened or started containers.
 For toxicological standards, consult FICHA DE SEGURIDAD.
 Apply with good air renewal.
 Shake contents of containers before use.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 31-10-2019 This sheet replaces all previous versions.

PINTURA EPOXI SUELOS AL DISOLVENTE TINTOMETRIA

