



# ANTI-RUST METAL PAINT

**WHITE**

Nitromors Smooth Metal Paint is for use on metal doors, metal garden furniture, metal gates and railings, no primer is required. Excellent resistance to UV and colour fading. For use on both ferrous and non-ferrous metal substrates. The powerful formulation will provide rust protection and salt spray resistance.



## HOW TO USE

1. Ensure area to be painted is free from dust, flakes of rust, grime, greases, and oils etc. by abrading the surface where required and wipe with a cloth dampened with white spirit.
2. Allow to dry.
3. Shake the can for at least 2 minutes, repeat shaking at regular intervals during use.
4. Apply sparingly from a distance of 15-25cm. Apply 2 to 3 light coats as necessary to achieve total and even coverage, leaving 15 minutes between each application.
5. Allow to dry for 24 hours to develop the maximum paint hardness.
6. On completion of use, invert the can and depress the nozzle for a few seconds to prevent nozzle blockage.

■ Appearance	Coloured liquids with characteristic paint odours.
■ Specific Gravity	0.900 to 0.955
■ Viscosity	Medium Viscosity liquids.
■ Active Content % m/m	10 to 25
■ Flammability	Extremely flammable aerosol.
■ Composition Data	Solvent based solutions of alkyd and acrylic resins containing xylene, acetone, pigments, driers, plasticisers and wetting agents dispersed in a liquefied propellant.

Product Code	Size	Barcode
NWI500	500ml	5010373143278



## ENVIRONMENTAL PROTECTION & SAFETY PRECAUTIONS



**Danger** - Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep out of reach of children. Use only outdoors or in a well ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Repeated exposure may cause skin dryness or cracking. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains Acetone, Xylene (mixture of isomers).

**CAUTION:** Pressurised container may burst if heated. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use. Do not spray on an open flame and other ignition sources. No smoking. Use only as directed.