



**FENICE S.p.A.**

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY  
+39 0445 424888      www.fenice.com

## TECHNICAL DATA SHEET – Leather Care Div.

# PLASTIC PRIMER S

### DESCRIPTION

**Plastic Primer S** is a solvent-based adhesion promoter designed for plastic car interiors.

### HOW TO USE

**Plastic Primer S** is an efficient product used as a primer before the renovation of plastic parts, due to its incredible adhesion, quick drying time and maximum transparency.

*Directions:* **Plastic Primer S** can be used by spray gun or by dabbing with a sponge directly on plastic, this way it's possible to minimize the quantity of product used and work without any waste.

The product is ready to go. Spray one abundant uniform coat and then proceed with the drying by using a heat gun.

PHYSICAL CONSTANTS	Standard Value	Test Method
Appearance	colourless liquid	MDA 008
Density (g/cm <sup>3</sup> )	0.71 ± 0.05	MDA 018
Flashpoint (°C)	<21	MDA 003

STORAGE	Rev.
Flammable product. Store at +5/40°C.	01.2019

### MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS

The product is guaranteed for its physical and quality characteristics 24 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.

All our information and suggestions are supplied on the basis of our present knowledge, and are subject to careful tests. However, we cannot accept responsibility for the use of the product, which must be verified and evaluated for its suitability or otherwise by the customer. Declared physical constants are monitored in production and guaranteed by FENICE S.p.A.