



**FENICE S.p.A.**

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY  
+39 0445 424888 www.fenice.com

**TECHNICAL DATA SHEET – Leather Care Div.**

**TOP COAT FAST / FISSATIVO RAPIDO**

**DESCRIPTION**

Topcoat Fast is a ready-to-use water-based product, ideal as a final step in refinishing automotive leather parts.

It guarantees excellent adhesion and allows the creation of a uniform layer on top of the leather.

Thanks to its advanced formulation, enriched with feel modifiers, the leather will be charming to the touch.

Topcoat Fast creates a medium-hard film with excellent physical and mechanical properties. These characteristics are improved even more with the necessary addition of Eco Crosslinker or Crosslinker AZ6.

After mixing the product with the Crosslinker, use the mixture within 8 hours.

**HOW TO USE**

Add the Crosslinker of choice. Apply the product by dabbing it with a sponge in the areas most difficult to be reached. Spray one or two coats (the second coat will improve the rub resistance).

It's highly recommended to speed up the drying process by using a heat gun or a different heat source to ensure the finishing layer's extended durability over time.

Apply any second layer immediately when the first one is completely dry.

<b>PHYSICAL CONSTANTS</b>	<b>Standard Value</b>	<b>Test Method</b>
Appearance	Whitish liquid	MDA 008
pH	8,5 ± 0.5	MDA 004
Density (g/cm <sup>3</sup> )	1.02 ± 0.05	MDA 018
Dry Content (%)	20 ± 2	MDA 010/011

**STORAGE**

Non-dangerous product. Store between +5/40°C.

**Rev.**

05.2021

**MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS**

The product is guaranteed for its physical and quality characteristics 24 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.