



**FENICE S.p.A.**

Via del Lavoro, 1 - 36078 Valdagno (Vicenza) - ITALY  
+39 0445 424888 www.fenice.com

**TECHNICAL DATA SHEET – Leather Care Div.**

**TOP COAT MATTE**

**DESCRIPTION**

Waterborne dull top coat to fix pigmented leather.

**HOW TO USE**

**Top Coat Matte** is a water-based dull fixing product for upholstery leathers, characterized by excellent adhesion and flowout.

It allows one to obtain a very uniform degree of opacity and high general fastness without greying. The resulting feel is very pleasant.

**Top Coat Matte** forms a medium-hard film with a slightly waxy feel and very good physical/mechanical properties that can be developed by using **Eco Crosslinker**.

**Top Coat Matte** mixed with **Eco Crosslinker** must to be used within 8 hours.

Sponge apply the product in difficult areas and then spray one light coat, or maximum two, if you want to increase rub resistance.

If possible, use a hairdryer to speed up drying. Spray the second coat immediately after the first one is dry.

PHYSICAL CONSTANTS	Standard Value	Test Method
Appearance	Whitish liquid	MDA 008
Dry content ( % )	20 ± 2	MDA 010/011
pH ( 1:10 )	8.0 ± 1	MDA 004
Density (g/cm <sup>3</sup> )	1.01 ± 0.05	MDA 018

STORAGE	Rev.
Non-dangerous product. Store between +5/40°C	07.2016

**MINIMUM SHELF-LIFE – HANDLING INSTRUCTIONS**

The product is guaranteed for its physical and quality characteristics 24 months from the date of production. It has to be kept in its original packaging, well sealed and stored following the conditions in our technical data.

This document is exclusively reserved for professional users.

All information regarding correct use and any hazardous content are available in the safety data sheets.