



TETROSEAL®

Underbody Sealant

Tetroseal Underbody Sealant has been specially formulated to protect vehicles against corrosion, rust, stones, salt and water, extending the vehicle life and helping to maintain value.

Tetroseal is a technologically advanced, highly structured underbody sealing compound which is particularly resistant to sagging during application, and provides excellent sound deadening qualities.

How to use:

1. Ensure the surface to be treated is dry and free from old flaking underbody sealant, loose rust, dirt & grease.
2. Mask off grease nipples, etc., with tape or newspaper.
3. Apply Underbody Sealant with a 7cm brush all over the underside of the vehicle, leaving about a 2mm coating.
4. After 2-3 hours, a second coat can be applied if desired.



ENVIRONMENTAL PROTECTION & SAFETY PRECAUTIONS

WARNING - Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY, LOW BOILING. Flammable liquid and vapour. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapours, spray. Do not eat, drink or smoke when using this product. Avoid release to the environment. Get medical advice/attention if you feel unwell. Dispose of contents/container in accordance with local regulations.



Technical Info

Appearance/Form:	Highly viscous liquid
Colour:	Black
Odour:	Solvent
Specific Gravity:	1.13g/cm ³ @ 20°C
Viscosity:	>10000mm ² /s @ 40°C
Flammability:	Flash Point 38°C
Solubility:	Insoluble in water

Product Code	Size	Barcode
TSL006	475g	5010373105726
TSL101	950g	5010372019789
TSL501	4.5kg	5010373105719