

ADDITIVE 51 ANTIGRAFFITI

Edition: 020 2011/11

Cod: 9000000051.00000.020

APPLICATION

The additive used on 2 K topcoats (URKI-NATO, URKI-NATO SAT, URKI-VOC and BESA-GLASS, U.S.) reduces the adhesion of dirt and improves the cleaning and the slippery properties of the surfaces painted with Graffiti.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,900 ± 0,005
V.O.C. (g/l)	900
Type of product	Silicone Polyacrilate
Colour	Transparent

SURFACE PREPARATION

Surface must be sanded with P320, degreased and let dry.

When recoating surfaces containing additive 51, make sure the surface is ready, to avoid loss of adhesion within layers

APPLICATION INSTRUCTIONS

Replace the recommended thinner on the Technical Data Sheet for the additive 51 Antigraffiti, and paint as indicated.

FEATURES OF DRY FILM

-	Allows an easier cleaning of the graffiti by high pressure water and soap or cleaning thinner SD-7 10.
---	--

Theoretical yield (m ² /l)	-
Gloss 60°-60°	-
Second layer	Only after sanding, degreased and completely dry.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.