

MAXI-FLEX

2 K POLYESTER PUTTY FOR PLASTICS

Edition: 021 2012/09
Cod: 5214007024.00000.021

APPLICATION

MASI-FLEX is a flexible Polyester Putty specially developed to repair plastic bumpers in cars: PC, PC-PBT, PP-EPDM. Outstands for its easy application, great filling power in dents and scratches, excellent sanding and fineness.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,85 ± 0,05
Grinding Fineness (µ)	
Supply viscosity at 20°C	Thixotropic
%Solids content (weight / volume)	89 % ± 2 weight; 75% ± 2 volume. (Mixture with hardener)
V.O.C. (g/l)	< 250 (Ready to use) - (2004/42/CE) IIB (B) (250)
Type of product	Polyester-Peroxide
Colour	Grey 7024

SURFACE PREPARATION

The surface must be dry, free from dirt and thoroughly degreased. It may be repainted with any top coat once sealed with BESA-CAR or BESA-EXPRESS.

APPLICATION INSTRUCTIONS

Application: Spatula.

Note: Do not add too much hardener to avoid bleedings.



E-39
2-3 %



3-5'



1000-3000 my



30'



5'



P-120
P-220

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	
Gloss 60°-60°	Matt
Second layer	1 - 2 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended. Can life: **12 months** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.