

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** ProXL 2k Primer
- **Article number:** PRO2KPRIME
- **1.2 Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
PRO XL  
Second Avenue  
Chatham  
Kent  
ME4 5AU  
Tel: +44(0)1634823900  
Fax: +44(0)1634813807  
Email: info@pro-xl.co.uk
- **Further information obtainable from:** Department Product Safety
- **1.4 Emergency telephone number:**  
Tel: +44(0) 1634 823900 (08.00 / 17.00)  
+31 629058130 (24 h/d, 7 d/wk)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Aerosol 1 . . . H222-H229 Extremely flammable aerosol, Pressurised container; May burst if heated.



GHS05 corrosion

Eye Dam. 1 . . . H318 . . . Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2, H411 . . . Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 . . . H315 . . . Causes skin irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20; . . . Harmful by inhalation.



F+; Extremely flammable

R12; . . . Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 1)

- **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
Warning! Pressurized container.
- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS05 GHS09

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
*butan-1-ol*
- **Hazard statements**  
H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*  
H315 *Causes skin irritation.*  
H318 *Causes serious eye damage.*  
H411 *Toxic to aquatic life with long lasting effects.*
- **Precautionary statements**  
P101 *If medical advice is needed, have product container or label at hand.*  
P102 *Keep out of reach of children.*  
P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*  
P211 *Do not spray on an open flame or other ignition source.*  
P251 *Do not pierce or burn, even after use.*  
P260 *Do not breathe spray.*  
P280 *Wear eye protection / face protection.*  
P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*  
P310 *Immediately call a POISON CENTER/doctor.*  
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*  
P501 *Dispose of contents / container in accordance with regional regulations.*
- **Additional information:**  
*Contains Esters der Methacrylsäure. May produce an allergic reaction.*  
*Buildup of explosive mixtures possible without sufficient ventilation.*
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterization: Mixtures**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*
- **Dangerous components:**

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 2)

CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether F+ R12 Flam. Gas 1, H220; Press. Gas, H280	25-<50%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	10-<12.5%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers Xn R20/21;  Xi R38 R10 Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Xn R20-48/20-65;  F R11 Flam. Liq. 2, H225;  STOT RE 2, H373; Asp. Tox. 1, H304;  Acute Tox. 4, H332; Aquatic Chronic 3, H412	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 Flam. Liq. 3, H226;  STOT SE 3, H336	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Xn R22;  Xi R37/38-41 R10-67 Flam. Liq. 3, H226;  Eye Dam. 1, H318;  Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-<5.0%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20;  Xi R36/37;  F R11 R66 Flam. Liq. 2, H225;  Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5.0%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1 Reg.nr.: 01-2119475133-43	Naphtha (petroleum), hydrotreated light Xn R65;  Xi R38;  F R11;  N R51/53 R67 Flam. Liq. 2, H225;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; STOT SE 3, H336	<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	<2.5%
	Esters der Methacrylsäure Xi R43 Skin Sens. 1, H317	≤0.5%

**Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex I 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 3)

- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, bluspoeder of waterstraal. Grotere brand met waterstraal of met schuim.  
Vaten met water afkoelen.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters -**
- **Protective equipment:**  
No special measures required.  
Mouth respiratory protective device.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.  
Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**  
Do not flush with water or aqueous cleansing agents  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 4)

- **Further information about storage conditions:**  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Storage class: 2B**
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

##### **115-10-6 dimethyl ether**

WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
-----	---

##### **1330-20-7 xylene, mixture of isomers**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

##### **100-41-4 ethylbenzene**

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

##### **123-86-4 n-butyl acetate**

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
-----	---

##### **71-36-3 butan-1-ol**

WEL	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

##### **108-10-1 4-methylpentan-2-one**

WEL	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm Sk, BMGV
-----	--

##### **108-65-6 2-methoxy-1-methylethyl acetate**

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
-----	--

- **Ingredients with biological limit values:**

##### **1330-20-7 xylene, mixture of isomers**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

##### **108-10-1 4-methylpentan-2-one**

BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
------	--

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 5)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**  
Not necessary if room is well-ventilated.  
Otherwise, filter class A / P2 or self contained.
- **Protection of hands:**



Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
Natural rubber, NR  
Butyl rubber, BR
- **Penetration time of glove material**  
Butyl rubber gloves with a thickness of 0.4 mm are resistant to:  
Acetone: 480 min  
Butyl acetate: 60 min  
Ethyl acetate: 170 min  
Xylene: 42 min
- **Eye protection:** Safety glasses

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
- **Flash point:** Not applicable, as aerosol.
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 235 °C
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

Trade name: ProXL 2k Primer

(Contd. of page 6)

· <b>Explosion limits:</b>	
<b>Lower:</b>	3.0 Vol %
<b>Upper:</b>	18.6 Vol %
· <b>Vapour pressure at 20 °C:</b>	5200 hPa
· <b>Density at 20 °C:</b>	1.06 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC-(EU)</b>	---
	818.2 g/l
· <b>VOC-EU%</b>	77.51 %
· <b>Solids content:</b>	27.5 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**7779-90-0 trizinc bis(orthophosphate)**

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

**1330-20-7 xylene, mixture of isomers**

Oral	LD50	8700 mg/kg (rat)
------	------	------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

Inhalative	LC50/4 h	6350 mg/l (rat)
------------	----------	-----------------

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
------	------	------------------

Dermal	LD50	17800 mg/kg (rabbit)
--------	------	----------------------

**71-36-3 butan-1-ol**

Oral	LD50	2292 mg/kg (rat) (OECD- Prüfrichtlinie 401))
------	------	--

		3430 mg/kg (rabbit) (OECD- Prüfrichtlinie 402)
--	--	--

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 7)

Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitizing effect by skin contact is possible by prolonged exposure.
- **Additional toxicological information:**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Harmful  
Vapours have narcotic effect.

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

#### **1330-20-7 xylene, mixture of isomers**

EC50 (24h)	>175 mg/l (bacteria)
EC50 / 48h	3.82 mg/l (daphnia magna / Wasserfloh)
EC50/72h	4.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	7.6 mg/l (oncorhynchus mykiss / Regenbogenforelle)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015




Version number 1

Revision: 15.01.2015

Trade name: ProXL 2k Primer

(Contd. of page 8)

### SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR  · IMDG · IATA	UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es) · ADR	
 	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	No Symbol (fish and tree)
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Gases. - F-D,S-U
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

GB

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

Trade name: ProXL 2k Primer

(Contd. of page 9)

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
  - H225 Highly flammable liquid and vapour.
  - H226 Flammable liquid and vapour.
  - H280 Contains gas under pressure; may explode if heated.
  - H302 Harmful if swallowed.
  - H304 May be fatal if swallowed and enters airways.
  - H312 Harmful in contact with skin.
  - H315 Causes skin irritation.
  - H317 May cause an allergic skin reaction.
  - H318 Causes serious eye damage.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H335 May cause respiratory irritation.
  - H336 May cause drowsiness or dizziness.
  - H373 May cause damage to organs through prolonged or repeated exposure.
  - H400 Very toxic to aquatic life.
  - H410 Very toxic to aquatic life with long lasting effects.
  - H411 Toxic to aquatic life with long lasting effects.
  - H412 Harmful to aquatic life with long lasting effects.
- 
- R10 Flammable.
  - R11 Highly flammable.
  - R12 Extremely flammable.
  - R20 Harmful by inhalation.
  - R20/21 Harmful by inhalation and in contact with skin.
  - R22 Harmful if swallowed.
  - R36/37 Irritating to eyes and respiratory system.
  - R37/38 Irritating to respiratory system and skin.
  - R38 Irritating to skin.
  - R41 Risk of serious damage to eyes.
  - R43 May cause sensitisation by skin contact.
  - R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
  - R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - R65 Harmful: may cause lung damage if swallowed
  - R66 Repeated exposure may cause skin dryness or cracking.
  - R67 Vapours may cause drowsiness and dizziness.

· **Contact:** Anwendungstechnik

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO: International Civil Aviation Organization  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.01.2015

Version number 1

Revision: 15.01.2015

**Trade name: ProXL 2k Primer**

(Contd. of page 10)

*GHS: Globally Harmonized System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**Flam. Gas 1: Flammable gases, Hazard Category 1**Flam. Aerosol 1: Flammable aerosols, Hazard Category 1**Press. Gas: Gases under pressure: Compressed gas**Flam. Liq. 2: Flammable liquids, Hazard Category 2**Flam. Liq. 3: Flammable liquids, Hazard Category 3**Acute Tox. 4: Acute toxicity, Hazard Category 4**Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2**Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1**Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2**Skin Sens. 1: Sensitisation - Skin, Hazard Category 1**STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3**STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2**Asp. Tox. 1: Aspiration hazard, Hazard Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3*

GB