

# ProALU

## Alu Primer Spray

PROALU provides excellent adhesion and corrosion prevention. Quick drying. Formulated for refinishing of OEM plated aluminium car bodies.

- Fast drying
- Excellent corrosion protection
- High adhesion on aluminium surfaces
- Supplied with 2 nozzles

### Suitable substrates

Aluminium,

### Application data



Apply 2 light coats from a distance of 250mm



Recoat after 15 minutes @ 20°C



5 - 8 Minutes



PRIMER BASECOAT SOLID COLOUR

### Application method



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.



# ProALU

## Alu Primer Spray

### Technical data

Chemical base	Special Mix of Resin
VOC content	321 g/500ml
Coverage	1.2m <sup>2</sup>
Storage notes	Empty cans 36 month. Relative air humidity of max. 60%)

### Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

### Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

