

# GREY UNDERCOAT

Code: PROWSGU

## Grey Undercoat Primer

PROWHEEL Grey Undercoat is a premium coloured undercoat wheel primer for fast spot priming under difficult covering topcoats, offering ultimate adhesion direct onto many difficult substrates including alloy, stainless steel, zintec and galvanise.

- Coloured spot primer for greater topcoat opacity
- Excellent adhesion and anti-corrosive properties
- Very fast drying
- Excellent smooth surface finish

## Suitable substrates

Suitably prepared Aluminium, Stainless Steel and Galvanised steel.

## Application Data



Shake aerosol for at least two minutes, after agitator ball is free.



Apply in cross coats from distance of 250mm from object.



Drying time 10-25 minutes.



After use turn aerosol upside down and empty valve.

**VOC** ✓



400ml



scroll down to continue

# GREY UNDERCOAT

Code: PROWSGU

## Technical Data

Chemical base	Nitro Cellulose Resin
VOC content	338 g/400ml
Coverage	1.0m <sup>2</sup>
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

### Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

### Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.



**400ml**

