

ProWELD

Weld Through Primer

PROWELD is a zinc aluminium welding primer, suitable for repairing damaged galvanising. It provides outstanding corrosion protection and is resistant to high temperatures.

- Weld through primer with excellent adhesion
- Very good cathodic corrosion prevention
- Resistant to petrol, chemicals and weather influences
- Compatible with SPOT, MIG and TIG welding methods
- Supplied with 2 nozzles

Application data



2-3 coats @ 40-60µm



Air dry 45 minutes @ 20°C
Overcoatable 20 minutes wet on wet



5-8 minutes



PROBUILD, PROPRIME, PRO2KPRIME

Application method



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.



ProWELD

Weld Through Primer

Technical data

Chemical base	Call us for detail
VOC content	340g/500ml
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

