



DRIVING SURFACE PERFECTION

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Product Reference code: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
SDS Ref. (EU): S2085-SDS  
Issue date: 03/03/2015 Revision date: 31/08/2020 Supersedes version of: 20/08/2019 Version: 3.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT  
UFI : U0X0-D0YP-D004-N77H  
Product code : S2085/1, S2085/5  
Product group : Clearcoat

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Coatings and paints, thinners, paint removers  
Function or use category : Topcoat

#### 1.2.2. Uses advised against

Restrictions on use : Consumer uses: Private households (= general public = consumers)

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

U-POL Limited  
Denington Road  
NN8 2QH Wellingborough - United Kingdom  
T +44 (0) 1933 230310  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### Importer

U-POL Netherlands B.V.  
Hoogoorddreef 15  
1101BA Amsterdam - Netherlands  
T +31 20 240 2216  
[technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: +44 (0) 870 8200418 (24 hrs)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	NHS England, Scotland & Wales	-	Call 111 or a Doctor	In Northern Ireland, contact your local GP or pharmacist during normal hours ( <a href="http://www.gpoutofhours.hscni.net">www.gpoutofhours.hscni.net</a> )

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 1 H318  
Skin sensitisation, Category 1 H317

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific target organ toxicity — Single exposure, Category 3, Narcosis H336

Full text of H statements : see section 16

### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

Unknown acute toxicity (CLP) - SDS

- : Danger
- : cyclohexanone; n-butyl acetate; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate; reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
- : H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H336 - May cause drowsiness or dizziness.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 - Avoid breathing spray, vapours.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- : 19% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## 2.3. Other hazards

Component	
cyclohexanone (108-94-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethyl methyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
cyclohexanone substance with a Community workplace exposure limit	(CAS-No.) 108-94-1 (EC-No.) 203-631-1 (EC Index-No.) 606-010-00-7 (REACH-no) 01-2119453616-35	25 – 50	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318
n-butyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336
ethyl methyl ketone substance with a Community workplace exposure limit	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-methylpentan-2-one; isobutyl methyl ketone substance with a Community workplace exposure limit	(CAS-No.) 108-10-1 (EC-No.) 203-550-1 (EC Index-No.) 606-004-00-4 (REACH-no) 01-2119473980-30	5 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335
Xylene substance with a Community workplace exposure limit (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	(EC-No.) 400-830-7 (EC Index-No.) 607-176-00-3 (REACH-no) 01-0000015075-76	0.1 – 0.25	Skin Sens. 1A, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5 (EC-No.) 915-687-0 (REACH-no) 01-2119491304-40	0.1 – 0.25	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage. Contain released product, pump into suitable containers.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing vapours, spray, fume. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Storage temperature	: < 25 °C
Storage area	: Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m <sup>3</sup>
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Ireland - Occupational Exposure Limits	
Local name	Butyl acetate
OEL TWA [1]	710 mg/m <sup>3</sup>
OEL TWA [2]	150 ppm
OEL STEL	950 mg/m <sup>3</sup>
OEL STEL [ppm]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2020

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>n-butyl acetate (123-86-4)</b>	
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

<b>cyclohexanone (108-94-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Cyclohexanone
IOEL TWA	40.8 mg/m <sup>3</sup>
IOEL TWA [ppm]	10 ppm
IOEL STEL	81.6 mg/m <sup>3</sup>
IOEL STEL [ppm]	20 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

<b>Ireland - Occupational Exposure Limits</b>	
Local name	Cyclohexanone
OEL TWA [1]	40.8 mg/m <sup>3</sup>
OEL TWA [2]	10 ppm
OEL STEL	81.6 mg/m <sup>3</sup>
OEL STEL [ppm]	20 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020

<b>Ireland - Biological limit values</b>	
Local name	Cyclohexanone
BLV	8 mg/l Parameter: cyclohexanol - Medium: urine - Sampling time: End of shift - Notations: Cyclohexanol= metabolite; Ns (Non-specific) 80 mg/l Parameter: 1,2-Cyclohexanediol - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Cyclohexanone
WEL TWA (OEL TWA) [1]	41 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	10 ppm
WEL STEL (OEL STEL)	82 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	20 ppm

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexanone (108-94-1)	
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Cyclohexanone
BMGV	2 mmol/mol Creatinine Parameter: cyclohexanol - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
ethyl methyl ketone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m <sup>3</sup>
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m <sup>3</sup>
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Methyl ethyl ketone (MEK)
OEL TWA [1]	600 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
Ireland - Biological limit values	
Local name	Butan-2-one
BLV	70 µmol/l Parameter: butan-2- one - Medium: urine - Sampling time: Post shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Butan-2-one (methyl ethyl ketone)
WEL TWA (OEL TWA) [1]	600 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	899 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	300 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ethyl methyl ketone (78-93-3)</b>	
<b>United Kingdom - Biological limit values</b>	
Local name	Butan-2-one (methyl ethyl ketone)
BMGV	70 µmol/l Parameter: butan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	4-Methylpentan-2-one
IOEL TWA	83 mg/m <sup>3</sup>
IOEL TWA [ppm]	20 ppm
IOEL STEL	208 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methyl isobutyl ketone (MIBK) [Hexone, Isobutyl methyl keton, 4-Methylpentan-2-one]
OEL TWA [1]	83 mg/m <sup>3</sup>
OEL TWA [2]	20 ppm
OEL STEL	208 mg/m <sup>3</sup>
OEL STEL [ppm]	50 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Methyl isobutyl ketone (MIBK)/ 4-methylpentan-2-one
BLV	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: End of shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	4-Methylpentan-2-one
WEL TWA (OEL TWA) [1]	208 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	4-methylpentan-2-one
BMGV	20 µmol/l Parameter: 4-methylpentan-2-one - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE



# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Xylene (1330-20-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Xylene, mixed isomers
OEL TWA [1]	221 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	442 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Ireland - Biological limit values</b>	
Local name	Xylene
BLV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	441 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>United Kingdom - Biological limit values</b>	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.1.2. Recommended monitoring procedures

No additional information available

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>n-butyl acetate (123-86-4)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	11 mg/kg bw/day
Acute - systemic effects, inhalation	600 mg/m <sup>3</sup>
Acute - local effects, inhalation	600 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11 mg/kg bw/day
Long-term - systemic effects, inhalation	300 mg/m <sup>3</sup>
Long-term - local effects, inhalation	300 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	6 mg/kg bw/day
Acute - systemic effects, inhalation	300 mg/m <sup>3</sup>
Acute - systemic effects, oral	2 mg/kg bw/day
Acute - local effects, inhalation	300 mg/m <sup>3</sup>
Long-term - systemic effects, oral	2 mg/kg bw/day
Long-term - systemic effects, inhalation	35.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	6 mg/kg bw/day
Long-term - local effects, inhalation	35.7 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.0903 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	35.6 mg/l

<b>cyclohexanone (108-94-1)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, dermal	100 mg/kg bodyweight/day
Acute - systemic effects, inhalation	100 mg/m <sup>3</sup>
Acute - local effects, inhalation	100 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	10 mg/kg bw/day
Long-term - systemic effects, inhalation	20 mg/m <sup>3</sup>
Long-term - local effects, inhalation	20 mg/m <sup>3</sup>

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, dermal	30 mg/kg bw/day
Acute - systemic effects, inhalation	50 mg/m <sup>3</sup>
Acute - systemic effects, oral	10 mg/kg bw/day
Acute - local effects, inhalation	50 mg/m <sup>3</sup>
Long-term - systemic effects, oral	5 mg/kg bw/day
Long-term - systemic effects, inhalation	50 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	20 mg/kg bw/day
Long-term - local effects, inhalation	20 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.033 mg/l
PNEC aqua (marine water)	0.003 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.168 mg/kg dwt
PNEC sediment (marine water)	0.017 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0.014 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l

<b>ethyl methyl ketone (78-93-3)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	600 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	31 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	106 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	55.8 mg/l
PNEC aqua (marine water)	55.8 mg/l
PNEC aqua (intermittent, freshwater)	55.8 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	284.74 mg/kg dwt
PNEC sediment (marine water)	284.7 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	22.5 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	1000 mg/kg food

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PNEC (STP)</b>	
PNEC sewage treatment plant	709 mg/l

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	208 mg/m <sup>3</sup>
Acute - local effects, inhalation	208 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	11.8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m <sup>3</sup>
Long-term - local effects, inhalation	83 mg/m <sup>3</sup>

<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	155.2 mg/m <sup>3</sup>
Acute - local effects, inhalation	155.2 mg/m <sup>3</sup>
Long-term - systemic effects, oral	4.2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.7 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	4.2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14.7 mg/m <sup>3</sup>

<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.6 mg/l
PNEC aqua (marine water)	0.06 mg/l
PNEC aqua (intermittent, freshwater)	1.5 mg/l

<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	8.27 mg/kg dwt
PNEC sediment (marine water)	0.83 mg/kg dwt

<b>PNEC (Soil)</b>	
PNEC soil	1.3 mg/kg dwt

<b>PNEC (STP)</b>	
PNEC sewage treatment plant	27.5 mg/l

### reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.05 mg/kg bw/day
Long-term - systemic effects, inhalation	0.35 mg/m <sup>3</sup>

<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.025 mg/kg bw/day
Long-term - systemic effects, inhalation	0.085 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0.25 mg/kg bw/day

<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.0023 mg/l

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PNEC aqua (marine water)	0.00023 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3.37 mg/kg dwt
PNEC sediment (marine water)	0.337 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	10 mg/l

### reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

#### DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation	0.68 mg/m <sup>3</sup> (DGUV DNEL List 2019)
--	--

#### Xylene (1330-20-7)

##### DNEL/DMEL (Workers)

Acute - systemic effects, inhalation	289 mg/m <sup>3</sup>
Acute - local effects, inhalation	289 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	180 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	77 mg/m <sup>3</sup>
Long-term - local effects, inhalation	77 mg/m <sup>3</sup>

##### DNEL/DMEL (General population)

Acute - systemic effects, inhalation	174 mg/m <sup>3</sup>
Acute - local effects, inhalation	174 mg/m <sup>3</sup>
Long-term - systemic effects, oral	1.6 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.8 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	108 mg/kg bodyweight/day
Long-term - local effects, inhalation	65.3 mg/m <sup>3</sup>

#### PNEC (Water)

PNEC aqua (freshwater)	0.327 mg/l
PNEC aqua (marine water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	12.46 mg/kg dwt
PNEC sediment (marine water)	12.46 mg/kg dwt

#### PNEC (Soil)

PNEC soil	2.31 mg/kg dwt
-----------	----------------

#### PNEC (STP)

PNEC sewage treatment plant	6.58 mg/l
-----------------------------	-----------

### 8.1.5. Control banding

No additional information available

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Gas mask. Gloves. Protective clothing. Safety glasses.

**Personal protective equipment symbol(s):**



##### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

##### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

**Other skin protection**

**Materials for protective clothing:**

Impermeable clothing

##### 8.2.2.3. Respiratory protection

**Respiratory protection:**

Air-fed respiratory protective equipment should be worn when this product is sprayed

##### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: Liquid.
Odour	: aromatic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Boiling point	: > 35 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: < 0 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: insoluble in water. soluble in most organic solvents.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 0.92 (0.91 – 0.93) g/cm <sup>3</sup>
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

VOC content : 753 g/l

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 753 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>n-butyl acetate (123-86-4)</b>	
LD50 oral rat	10760 – 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	390 ppm/4h
LC50 Inhalation - Rat (Vapours)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)

<b>cyclohexanone (108-94-1)</b>	
LD50 oral rat	1890 mg/kg bodyweight (BASF test, Rat, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	1100 mg/kg (BRENNTAG test)
LC50 Inhalation - Rat	> 6.2 mg/l air Animal: rat
LC50 Inhalation - Rat (Vapours)	8000 mg/l/4h

<b>ethyl methyl ketone (78-93-3)</b>	
LD50 oral rat	2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LD50 oral rat	2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27
LD50 dermal rat	≥ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat (Vapours)	10 – 20 mg/l/4h

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LD50 oral rat	> 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female)
LD50 dermal rat	> 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
LC50 Inhalation - Rat	5800 mg/l (OECD Guideline 403, 14d, rat)

<b>reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>	
LD50 oral rat	3230 mg/kg (OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), rat, male/female)



# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 dermal rat	> 3170 mg/kg (OECD Guideline 402 (Acute Dermal Toxicity), read-across,
-----------------	--

<b>toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat	25.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Vapours)	25.7 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male, Experimental value, Inhalation (vapours))

<b>cellulose acetate butyrate (9004-36-8)</b>	
LD50 oral rat	> 3200 mg/kg
LD50 dermal	> 1000 mg/kg (Guinea pig)

<b>2-phenoxyethanol (122-99-6)</b>	
LD50 oral rat	1850 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	14391 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2214 mg/kg bodyweight Animal: rabbit, Guideline: other:Draft IRLG (Interagency Regulatory Liaison Group) Guidelines for Selected Acute Toxicity Tests (August. 1979)
LC50 Inhalation - Rat	> 1 mg/l air Animal: rat, Guideline: other:OECD 412

<b>Xylene (1330-20-7)</b>	
LD50 oral rat	3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days)
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
LC50 Inhalation - Rat [ppm]	6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male)

<b>octamethylcyclotetrasiloxane (556-67-2)</b>	
LD50 oral rat	> 4800 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2400 mg/kg bodyweight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	36 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

<b>mixed dibasic acid polyester plasticizer</b>	
LD50 oral rat	> 5000 mg/kg

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	15432 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours))

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Unknown acute toxicity (CLP) - SDS : 19% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye damage.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

### cyclohexanone (108-94-1)

IARC group	3 - Not classifiable
------------	----------------------

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

### Xylene (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified

### 2-phenoxyethanol (122-99-6)

LOAEL (animal/male, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
LOAEL (animal/female, F1)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP
NOAEL (animal/female, F0/P)	≈ 1875 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: other:Reproductive Assessment by Continuous Breeding (RACB); protocol devised by the NTP

STOT-single exposure : May cause drowsiness or dizziness.

### n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### ethyl methyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### Xylene (1330-20-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>cyclohexanone (108-94-1)</b>	
NOAEL (oral, rat, 90 days)	143 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

<b>toluene (108-88-3)</b>	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>2-phenoxyethanol (122-99-6)</b>	
LOAEL (oral, rat, 90 days)	> 700 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	> 500 mg/kg bodyweight Animal: rabbit
NOAEL (oral, rat, 90 days)	700 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rabbit
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0482 mg/l/6h/day

<b>Xylene (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

<b>Ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing sense) through prolonged or repeated exposure.

Aspiration hazard : Not classified

### 11.2. Information on other hazards

No additional information available

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>n-butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	62 mg/l (Leuciscus idus, static system)
EC50 - Crustacea [1]	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	23 mg/l

<b>cyclohexanone (108-94-1)</b>	
LC50 - Fish [1]	527 – 732 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)

<b>ethyl methyl ketone (78-93-3)</b>	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna

<b>reaction mass of <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-hydroxypoly(oxyethylene) and <math>\alpha</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-<math>\omega</math>-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)</b>	
LC50 - Fish [1]	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 - Crustacea [1]	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 algae	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

### Xylene (1330-20-7)

LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 72h - Algae [1]	2.2 mg/l
ErC50 algae	4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

## 12.2. Persistence and degradability

### n-butyl acetate (123-86-4)

Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.46

### cyclohexanone (108-94-1)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.232 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.605 g O <sub>2</sub> /g substance
ThOD	2.605 g O <sub>2</sub> /g substance

### ethyl methyl ketone (78-93-3)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.31 g O <sub>2</sub> /g substance
ThOD	2.44 g O <sub>2</sub> /g substance

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.06 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.16 g O <sub>2</sub> /g substance
ThOD	2.72 g O <sub>2</sub> /g substance

### Xylene (1330-20-7)

Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
-------------------------------	--

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.3. Bioaccumulative potential

#### n-butyl acetate (123-86-4)

BCF - Fish [1]	15.3 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### cyclohexanone (108-94-1)

BCF - Other aquatic organisms [1]	2.4 (QSAR)
Partition coefficient n-octanol/water (Log Pow)	0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### ethyl methyl ketone (78-93-3)

Partition coefficient n-octanol/water (Log Pow)	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

BCF - Fish [1]	2658 – 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	4.6 (Experimental value, Equivalent or similar to OECD 117, 25 °C)

#### Xylene (1330-20-7)

BCF - Fish [1]	7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across)
Partition coefficient n-octanol/water (Log Pow)	3.2 (Read-across, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

#### n-butyl acetate (123-86-4)

Surface tension	0.0163 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.268 – 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

#### cyclohexanone (108-94-1)

Surface tension	0.034 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ecology - soil	Highly mobile in soil.
----------------	------------------------

ethyl methyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Partition coefficient n-octanol/water (Log Koc)	1.53 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Partition coefficient n-octanol/water (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

Xylene (1330-20-7)	
Surface tension	28.01 – 29.76 mN/m (25 °C)
Partition coefficient n-octanol/water (Log Koc)	2.73 (log Koc, Equivalent or similar to OECD 121, Read-across)
Ecology - soil	Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation.

### 12.5. Results of PBT and vPvB assessment

Component	
cyclohexanone (108-94-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethyl methyl ketone (78-93-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Xylene (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 14.1. UN number or ID number

UN-No. (ADR)	: UN 1263
UN-No. (IMDG)	: UN 1263
UN-No. (IATA)	: UN 1263
UN-No. (ADN)	: UN 1263
UN-No. (RID)	: UN 1263

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PAINT
Proper Shipping Name (IMDG)	: PAINT
Proper Shipping Name (IATA)	: Paint
Proper Shipping Name (ADN)	: PAINT
Proper Shipping Name (RID)	: PAINT
Transport document description (ADR)	: UN 1263 PAINT, 3, II, (D/E)
Transport document description (IMDG)	: UN 1263 PAINT, 3, II
Transport document description (IATA)	: UN 1263 Paint, 3, II
Transport document description (ADN)	: UN 1263 PAINT, 3, II
Transport document description (RID)	: UN 1263 PAINT, 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



#### IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



#### IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3



#### ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3



#### RID

Transport hazard class(es) (RID)	: 3
----------------------------------	-----



# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danger labels (RID) : 3



### 14.4. Packing group

Packing group (ADR) : II  
Packing group (IMDG) : II  
Packing group (IATA) : II  
Packing group (ADN) : II  
Packing group (RID) : II


### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 163, 367, 640D, 650  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02, R001  
Special packing provisions (ADR) : PP1  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T4  
Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

#### Transport by sea

Special provisions (IMDG) : 163, 367  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
Special packing provisions (IMDG) : PP1  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T4  
Tank special provisions (IMDG) : TP1, TP8, TP28  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : B  
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

#### Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

### Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640D, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640D, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:		
Reference code	Applicable on	Entry title or description
3(a)	SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT ; Xylene ; ethyl methyl ketone ; isobutyl methyl ketone ; cyclohexanone ; n-butyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3(b)	SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT ; Xylene ; ethyl methyl ketone ; isobutyl methyl ketone ; cyclohexanone ; n-butyl acetate ; reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ; reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT ; Xylene ; ethyl methyl ketone ; isobutyl methyl ketone ; cyclohexanone ; n-butyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list  $\geq 0,1\%$  / SCL

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 753 g/l

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

### Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2

# SYSTEM 20 1K ACRYLIC SMART CLEAR UV RESISTANT CLEARCOAT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).