



S2085 – 1K ACRYLIC SMART CLEAR

UV RESISTANT CLEAR COAT

FEATURES & BENEFITS	<p>1K SMART CLEAR is a crystal clear 1K, ready to use clear coat. 1K SMART CLEAR is used for finishing coated surfaces in order to achieve a high gloss, UV resistant, durable finish.</p> <p>1K SMART CLEAR is a new high performance clear coat that gives 2K performance with the convenience of a single pack. 1K SMART CLEAR is the ultimate SMART repair tool with excellent build, flow out and gloss retention. 1K SMART CLEAR is compatible with most paint systems including water-based.</p> <p>The cured clear has excellent gloss and image depth and is ideal for spot repairs and complete resprays resulting in a durable, UV resistant finish.</p> <p>1K SMART CLEAR is isocyanate free.</p>
HEALTH AND SAFETY STATEMENT	<p>FOR PROFESSIONAL USE ONLY. Read full instructions before use.</p> <p>IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.</p>
SURFACE PREPARATION	<p>1K SMART CLEAR can be applied using the preparation procedure shown below: -</p> <p>Thoroughly clean and degrease surfaces with a suitable panel wipe such as U-POL System 20 Degreaser. Abrade solid colour coatings wet or dry with 800-2000 abrasive, re-clean, dry and degrease. If coating solvent-based basecoats apply 1K SMART CLEAR within a period of 1 hour after application of the base coat.</p>
APPLICATION	<p>1K SMART CLEAR is ready for use and requires no thinning.</p> <p>Apply 2-3 even coats.</p> <p>Allow 5-10 minutes flash off time between coats.</p>
DRYING TIME	<p>Allow 30 minutes before handling.</p> <p>Drying time is dependent upon film thickness, humidity and temperature.</p>
Product Codes	<p>S2085/1 - 1 Litre S2085/5 - 5 Litre</p>

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 0EY, UK
Home Sales T: +44(0)870 899 8200; F:+44(0)870 899 8211; E: sales@u-pol.com;
Export Sales T: +44(0)870 899 8200; F:+44(0)870 899 8299; E: exportsales@u-pol.com;
Technical T: +44(0)870 899 8310; F:+44(0)870 899 8351; E: technicaldepartment@u-pol.com;
WEBSITE: WWW.U-POL.COM