



**SAFETY DATA SHEET**  
**Simoniz AA Yellow**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name                      Simoniz AA Yellow  
Product No.                         SIMP24D

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses                      Paint.

**1.3. Details of the supplier of the safety data sheet**

Supplier                                 Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
A Holts Car Care Product  
www.holtsauto.com

Contact Person                      Contact Email address: info@holtsauto.com

**1.4. Emergency telephone number**

UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167  
National Emergency Telephone Number  
<http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks>

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222+H229
Human health	EUH066; Eye Irrit. 2 - H319; STOT SE 3 - H336
Environment	Not classified.

Classification (1999/45/EEC)

Xi; R36. F+; R12. R66, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**2.2. Label elements**

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H222+H229	Extremely flammable aerosol.
H319	Pressurised container: May burst if heated.
H336	Causes serious eye irritation.
	May cause drowsiness or dizziness.

Precautionary Statements

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

## Simoniz AA Yellow

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P501	Dispose of contents/container in accordance with local regulations.
<b>Supplementary Precautionary Statements</b>	
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing vapour/spray.
P264	Wash contaminated skin thoroughly after handling.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P313	Get medical advice/attention.
P337	If eye irritation persists:
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
<b>Supplemental label information</b>	
EUH066	Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

ACETONE	30-60%
CAS-No.: 67-64-1	EC No.: 200-662-2
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R66 R67
DIMETHYL ETHER	10-30%
CAS-No.: 115-10-6	EC No.: 204-065-8
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
ETHYL ACETATE	5-10%
CAS-No.: 141-78-6	EC No.: 205-500-4
Classification (EC 1272/2008) Flam. Liq. 2 - H225 EUH066 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R66 R67

## Simoniz AA Yellow

BUTYL ACETATE -norm	5-10%
CAS-No.: 123-86-4	EC No.: 204-658-1
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336	Classification (67/548/EEC) R10 R66 R67
2-METHOXY-1-METHYLETHYL ACETATE	5-10%
CAS-No.: 108-65-6	EC No.: 203-603-9
Classification (EC 1272/2008) Flam. Liq. 3 - H226	Classification (67/548/EEC) R10 Xi;R36
ISOBUTANE	5-10%
CAS-No.: 75-28-5	EC No.: 200-857-2
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
BUTANE	5-10%
CAS-No.: 106-97-8	EC No.: 203-448-7
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
BUTANOL-norm	1-5%
CAS-No.: 71-36-3	EC No.: 200-751-6
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT SE 3 - H336	Classification (67/548/EEC) R10 Xn;R22 Xi;R37/38,R41 R67
PROPAN-2-OL	1-5%
CAS-No.: 67-63-0	EC No.: 200-661-7
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC) F;R11 Xi;R36 R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: FIRST AID MEASURES

## **4.1. Description of first aid measures**

Inhalation

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Not relevant

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Spray in the eyes: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## **4.2. Most important symptoms and effects, both acute and delayed**

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

Due to the physical nature of this material it is unlikely that swallowing will occur.

Skin contact

Prolonged skin contact may cause redness and irritation.

Eye contact

May cause temporary eye irritation.

## **4.3. Indication of any immediate medical attention and special treatment needed**

Treat Symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

Unusual Fire & Explosion Hazards

Risk of explosion if heated. If heated, volume and pressure increases strongly, resulting in explosion of container.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

For personal protection, see section 8.

### **6.2. Environmental precautions**

Not relevant considering the small amounts used.

### **6.3. Methods and material for containment and cleaning up**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. When dealing with a spillage, please consult the section relating to suitable protective measures.

### **6.4. Reference to other sections**

For personal protection, see section 8. See section 11 for more detailed information on health effects and symptoms. For waste disposal, see section 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

## Simoniz AA Yellow

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3	
ETHYL ACETATE	WEL	200 ppm		400 ppm		
ISOBUTANE	OES	800 ppm		800 ppm		
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Process conditions

Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. Rubber gloves are recommended. EN374

Eye protection

Use eye protection. Goggles/face shield are recommended.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

# Simoniz AA Yellow

Colour	Yellow.
Odour	Slight odour.
Solubility	Insoluble in water Immiscible with water
Relative density	0.748
pH-Value, Conc. Solution	
Not applicable.	
Flash point (°C)	<0
Auto Ignition Temperature (°C)	240
Flammability Limit - Lower(%)	4.8
Flammability Limit - Upper(%)	9.5

## **9.2. Other information**

### **SECTION 10: STABILITY AND REACTIVITY**

#### **10.1. Reactivity**

No specific reactivity hazards associated with this product.

#### **10.2. Chemical stability**

Stable under normal temperature conditions.

#### **10.3. Possibility of hazardous reactions**

Not applicable.

#### **10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### **10.5. Incompatible materials**

Materials To Avoid

No incompatible groups noted.

#### **10.6. Hazardous decomposition products**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **11.1. Information on toxicological effects**

Inhalation

When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

No harmful effects expected in amounts likely to be ingested by accident.

Skin contact

Prolonged and frequent contact may cause redness and irritation.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

### **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity

The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

#### **12.1. Toxicity**

#### **12.2. Persistence and degradability**

Degradability

The product is expected to be biodegradable.

**12.3. Bioaccumulative potential**

Bioaccumulative potential  
The product is not bioaccumulating.

**12.4. Mobility in soil**

Mobility:  
The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product is insoluble in water. The product hardens to a solid immobile substance.

**12.5. Results of PBT and vPvB assessment**

This product does not contain any PBT or vPvB substances.

**12.6. Other adverse effects**

Not known.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**


---

**13.1. Waste treatment methods**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

---

**SECTION 14: TRANSPORT INFORMATION**


---

**14.1. UN number**

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

**14.2. UN proper shipping name**

Proper Shipping Name                      AEROSOLS

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class	2.1
ADR/RID/ADN Class	Class 2: Gases
ADR Label No.	2.1
IMDG Class	2.1
ICAO Class/Division	2.1
Transport Labels	

**14.4. Packing group**

Not applicable.

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS    F-D, S-U

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

## Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

## EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

## National Regulations

Workplace Exposure Limits 2005 (EH40)

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are noted for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions of use are noted for this product.

## Water hazard classification

WGK 1

**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

**SECTION 16: OTHER INFORMATION**

Revision Date 17/06/2015

Revision 1

Date 15060

## Risk Phrases In Full

R12 Extremely flammable.  
 R10 Flammable.  
 R22 Harmful if swallowed.  
 R11 Highly flammable  
 R36 Irritating to eyes.  
 R37/38 Irritating to respiratory system and skin.  
 R66 Repeated exposure may cause skin dryness or cracking.  
 R41 Risk of serious damage to eyes.  
 R67 Vapours may cause drowsiness and dizziness.

## Hazard Statements In Full

H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H315 Causes skin irritation.  
 H222+H229 Extremely flammable aerosol.  
 Pressurised container: May burst if heated.  
 H220 Extremely flammable gas.  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H225 Highly flammable liquid and vapour.  
 H336 May cause drowsiness or dizziness.  
 H335 May cause respiratory irritation.  
 EUH066 Repeated exposure may cause skin dryness or cracking.