

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007








1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** COLORMATIC PRE-FILLED SPRAY CAN
- **Article number:** 570704
- **Application of the substance / the preparation** Preparation
- **Manufacturer/Supplier:**
MOTIP DUPLI B.V.
Wolfraamweg 2
NL- 8471 XC Wolvega
The Netherlands
Tel: +31 (0)561 694400
Fax: +31 (0)561 694411
e-mail info@nl.motipdupli.com
- **Further information obtainable from:** QHSE Department
- **Information in case of emergency:** Tel: +31 (0)561 694400

2 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether	 F+; R 12	50-75%
CAS: 67-64-1 EINECS: 200-662-2	acetone	 Xi,  F; R 11-36-66-67	25-50%
CAS: 1330-20-7 EINECS: 215-535-7	xylene	 Xn,  Xi; R 10-20/21-38	2.5-5%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol	 Xn,  Xi; R 10-22-37/38-41-67	2.5-5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· **Hazard description:**



Xi Irritant
F+ Extremely flammable

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: COLORMATIC PRE-FILLED SPRAY CAN

(Contd. of page 1)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First-aid measures

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Fire-fighting measures

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Person-related safety precautions:** Ensure adequate ventilation

· **Measures for environmental protection:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:** Ensure adequate ventilation.

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: **COLORMATIC PRE-FILLED SPRAY CAN**

(Contd. of page 2)

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

<i>WEL ()</i>	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
---------------	---

67-64-1 acetone

<i>WEL ()</i>	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
---------------	--

1330-20-7 xylene

<i>WEL ()</i>	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
---------------	--

71-36-3 butan-1-ol

<i>WEL ()</i>	Short-term value: 154 mg/m ³ , 50 ppm Sk
---------------	--

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:** Not required.

· **Material of gloves:** Not required.

· **Penetration time of glove material:** Not required.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· **Flash point:**

< 0°C (< 32°F)

Not applicable, as aerosol.

· **Ignition temperature:**

235.0°C (455°F)

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: **COLORMATIC PRE-FILLED SPRAY CAN**

(Contd. of page 3)

- | | |
|--|---|
| · Self-igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 2.6 Vol % |
| Upper: | 18.6 Vol % |
| · Vapour pressure at 20°C (68°F): | 4000.0 hPa (3000 mm Hg) |
| · Density at 20°C (68°F): | 0.72200 g/cm ³ |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Solvent content: | |
| Organic solvents: | 100.0 % |
| · EU-VOC: | 722.0 g/l |
| · EU-VOC in %: | 100.00 % |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

115-10-6 dimethyl ether

	LC50 / 4 h	308 mg/m ³ (rat)
--	------------	-----------------------------

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)
	LC50 / 4 h	39 mg/m ³ (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
	LC50 / 4 h	22.1 mg/m ³ (rat)

71-36-3 butan-1-ol

Oral	LD50	4400 mg/kg (rat)
Dermal	LD50	4200 mg/kg (rabbit)
	LC50 / 4 h	25 mg/m ³ (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

GB

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: **COLORMATIC PRE-FILLED SPRAY CAN**

(Contd. of page 4)

12 Ecological information

· Ecotoxicological effects:

· Aquatic toxicity:

115-10-6 dimethyl ether

EC50 / 48 h	>4000 mg/l (daphnia magna)
-------------	----------------------------

67-64-1 acetone

EC50 / 48 h	39 mg/l (daphnia magna)
LC50 / 48 h	2262 mg/l (daphnia magna)
LC50 / 96 h (static)	5540 mg/l (fish)

1330-20-7 xylene

EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

71-36-3 butan-1-ol

EC50 / 48 h	1983 mg/l (daphnia magna)
EC50 / 72 h	8500 mg/l (algae)

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 01 13	solvents
15 01 04	metallic packaging

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 2 5F Gases.
· Danger code (Kemler): 23
· UN-Number: 1950
· Packaging group: -
· Hazard label 2.1
· Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



· IMDG Class: 2.1

(Contd. on page 6)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: COLORMATIC PRE-FILLED SPRAY CAN

(Contd. of page 5)

- **UN Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

15 Regulatory information

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**



Xi Irritant
F+ Extremely flammable

- **Risk phrases:**

12 Extremely flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

- **Safety phrases:**

2 Keep out of the reach of children.
23 Do not breathe aerosol.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

- **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
Buildup of explosive mixtures possible without sufficient ventilation.
Keep out of the reach of children

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 7)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 28.03.2007

Reviewed on 16.03.2007

Trade name: COLORMATIC PRE-FILLED SPRAY CAN

(Contd. of page 6)

· Relevant R-phrases

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 22 Harmful if swallowed.
- 36 Irritating to eyes.
- 37/38 Irritating to respiratory system and skin.
- 38 Irritating to skin.
- 41 Risk of serious damage to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: QHSE Department**· Contact:**

Mrs. D. Kleistra

Mr. H.J. Hoogenberg

GB