

TECHNICAL DATA SHEET

J-25 Contract Matt

Code: 73150

APRIL 2015

DESCRIPTION

JUNO's J-25 Contract Matt is professional quality, high opacity, quick drying matt emulsion for both old and new surface areas. Acrylic copolymer based paint formulated with titanium dioxide and extenders.
Provides a tough and durable matt finish that is ideal for high traffic areas.
Wipeable and offers good stain resistance.
Suitable for all normal interior wall and ceiling surfaces.

USE: INTERIOR

Suitable for wall and ceiling decoration, and anywhere wet-rubbing resistance and a matt finish is required. Ideal for application on new plaster.

APPLICATION

Stir thoroughly before use.
Use Brush, roller, spray & airless spray.
On very absorbent surfaces apply a sealing coat of thinned J-25 Contract Matt.
Finishing: Apply 1 or 2 coats of J-25 Contract Matt.

As with other water-based paints, do not apply in temperatures below 5°C.
Due to occasional differences in absorption during the painting of gypsum surfaces, sealing the surface is recommended using AQUA-SELL, Code: 21203.
In case of pre-painted surfaces, any paint in poor condition must be removed, and deteriorated and chipped areas retouched with JUNO PLASTE, before the paint is applied.
Gloss or satin paints or varnishes must be sanded down until the gloss is removed, to improve bonding and adhesion.

TAKE THE FOLLOWING ACTION IN CASE OF:

- EFFLORESCENCE, SALTPETRE - Wash with vinegar or 10% Hydrochloric Acid diluted solution. Rinse with water and allow to dry.
- WEAK, PULVEROUS OR AREAS WITH DIFFERENT DEGREES OF ABSORPTION - Prime with Hidrokril Acrylic Sealer (81006), thinned with 4 parts of water and 1 part of Hidrokril.
- STAINS FROM DAMP, GREASE, SMOKE, NICOTINE, ETC.- Wash with water and detergent, and allow to dry.
Prime with JUNO's STAIN COVER (21350) or JUNO ANTI-DAMP COATING (21350).
- FUNGUS, ALGAE, MICRO-ORGANISMS - Wash with water and bleach. Allow to dry.
Prime with JUNOSAN Base Cleaner.
- FINE AND MAJOR CRACKS, UNEVEN SURFACES - Repair with JUNO Plaster.

THINNING

Sealing new/bare surfaces: Add up to 1 part clean water to 5 parts paint.
Normal use (not to be exceeded): Thinning is not required.
Conventional spray application: Add up to 1 part clean water to 5 parts paint.
Airless spray application: Thinning is not required.

OBSERVATIONS

Do not apply in ambient temperatures below 5° C.
Stir the recipient contents thoroughly until evenly mixed.
Working tools must be cleaned immediately after use with clean water.

APPLICATION PROCEDURE

Surfaces must be clean of dust, grease, oils, dirt, rust, waste or anything else that may contaminate the paint. Remove the paint, varnishes or old treatments in a poor state and if needed clean up the imperfection, area and exposition with an adequate filler.
Follow recommended application temperature and drying times between coats.(20°C, relative humidity 65%).
The thickness of application, temperature and humidity may affect drying times.
Buy only the necessary quantity required, taking into account the m², porosity and support texture. Store the remaining product in a dry and well-ventilated place. Work with the appropriate ventilation and respect the safety precautions norms indicated in the safety data sheet of the product.

The information contained in this data sheet may vary and must be updated. Please visit www.juno.es or consult with your nearest JUNO representative who will provide you with the most recent date sheet. Our technical instructions and advice whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, they must only be interpreted as indications WITHOUT LIABILITY even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the intended procedures and purposes. The application, use and processing of the products supplied by JUNO are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.

Finish: Matt

Color: White.

Viscosity: Min. 100 P S/FR1007

Density: 1,62 +/- 0,05 S/FR1001

Drying time: 1 hour to the touch
Repaint minimum 6 hours.
Maximum: undefined.

VOC's content: max 30 g/l.

Performance: 6 m² / L/ coat

Flash point: Non-flammable

Solids in volume: (40 +/-2)%
Theoretical

Fire reaction: B-s1,d0 (UNE 13501-1:2007).

SHIPPING



Packaging: 04/1 5liters
Shipping Weight:
Units per pallet: 120/33



Freight Classification:
Paint or paint related material



Transport Information
No restriction for transport
(ADR/RID, IMDG, IATA)

CLEANING

Clean the splash and stains immediately with soapy water or with an adequate solvent. Clean tools after use (brushes, rollers, pencils, machines etc.) and let them dry before storing. Consult your city council about the appropriate recycling method for the container, waste and excess paint, in accordance with the existing legislation and environmental protection principles.

