

PINTURAS JUNO

DATA SHEET

MULTIPURPOSE WHITE PRIMER

CODE: 27027

DESCRIPTION

A quick drying primer with anticorrosive properties, suitable for all types of substrates.

USAGE: INDOOR - OUTDOOR

Suitable for ferrous metals, steel, galvanised surfaces, wood (only indoor) and PVC, as a bonding primer and can be used as undercoat for any kind of enamel.

CHARACTERISTICS

- | | |
|----------------------------|--|
| • Finish | Semi-matt |
| • Colour | White |
| • Viscosity at 20° C | Min 40 Poises S/FR1007 |
| • Density at 20° C | 1.60 +/-0.05 g/cc S/FR1001 |
| • Drying time | To the touch: 45 minutes
Second coat: 6 hours |
| • Diluent | D-17 |
| • Solids in volume | 39 %. Theoretical |
| • VOC content | Maximum 600 g/Lt |
| • Coverage | 10 m ² / Lt approx. |

SURFACE PREPARATION

IRON

Remove rust and old paint.

STEEL

Clean grease and oil residues with solvent

GALVANISED SHEET Clean with solvent.

Given the varied range of galvanised finishes in the market, it is recommended to carry out a prior test.

WOOD (indoor)

Previous cleaning and sanding.

PVC

Use solvents or abrasive detergents to previously clean surfaces.



PINTURAS JUNO

Bº Sacconi, 10-48.950 Erandio (Vizcaya)-Tel. 94-467 00 62-Fax 94-467 58 32

INTERNET:www.juno.es - E-MAIL: infoweb@juno.es

APPLICATION INSTRUCTIONS

Brush, spray gun or airless spray gun. Maximum dilution: 10% in volume.

CLEANING

D-17 solvent

REPAINTING

Suitable for all types of paint. The use of an Universal Primer can be considered.

OBSERVATIONS

Approximately 6 hours after its application, **Multipurpose White Primer** can be covered with **Junolac Synthetic Enamel, Junosport Water Acrylic, Junokril, Castor** or any other plastic paint.

When applying **Epoxi 2/C Enamel, Junoretano 2/C Enamel** or **Junosport Chlororubber** finishes, spray painting is recommended.

Regardless of the time spent during application, **Multipurpose White Primer** has an advantage over the rest, as it retains its repainting capacity with any type of enamel, without the need of prior sanding.

PACKAGING

Lithographed metal container. Sizes: **0.750 / 4 and 15 litres**

Date: December 2006/Revision: 3

N.B.: Our technical instructions and advice, whether oral, in writing or through tests are given in good faith and to the best of our knowledge. However, it must only be construed as an indication **WITHOUT LIABILITY** even in regard to possible third-party industrial property rights, and this does not exempt the customer from testing the supplied products in order to verify their suitability for the procedures and purposes intended. The application, use and processing of the products supplied by us are carried out outside and beyond our control, and therefore, constitute the exclusive responsibility of the customer. If, however, there were any grounds to consider any liability on our part, this will be limited, regardless of the damage and loss, to the strict value of the goods supplied by us and used by the customer. It is understood that we guarantee the absolute quality of our products according to our General Sale and Supply Conditions.



PINTURAS JUNO

Bº Sacconi, 10-48.950 Erandio (Vizcaya)-Tel. 94-467 00 62-Fax 94-467 58 32

INTERNET:www.juno.es - E-MAIL: infoweb@juno.es