

URKI-KOMBI
1 K NC PUTTY

APPLICATION

URKI-KOMBI is a ready-to-use Putty, based on nitrocellulose resins. Designed for Spot Repair to collect minor imperfections such as scratches, blisters, pinholes, impacts, etc. It is also very effective in filling in small pinholes in spoilers and Fiberglass parts.

The product stands out for its:

- Easy application
- Fast drying
- Soft, silky and very flexible surface
- Lack of shrinkage in repaired areas

Can be applied on polyester putties or acrylic type primers and fillers. Also on steel, aluminum and zinc covered surfaces.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,68 ± 0,03
Grinding Fineness (μ)	Without lumps
Supply viscosity at 20°C	Tixotropic
V.O.C. (g/l)	< 250 (Ready to use) - (2004/42/CE) IIB (B) (250)
Type of product	Nitrocellulose
Colour	Grey 7035

SURFACE PREPARATION

The surface to be repaired must be degreased and sanded, both on metallic surfaces, putties and fillers.

APPLICATION INSTRUCTIONS

Application: Spatula.

Application in thin layers. Time between layers 20-30 min. Not recommended to exceed 70-80m total.



Maximum 80 m²
in thin layers



30-45'



P-240
P-400

FEATURES OF DRY FILM

Theoretical yield (m ² /l)	
Gloss 60°-60°	Matt
Second layer	1 h.

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

Can life: **12 months** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.