

URKI-PROTEC
ANTI STONE CHIP

Edition: 021 2013/01
Cod: 3700100000.00000.021

APPLICATION

URKI-PROTEC Anti Stone Chip provides a hard durable coating designed to match the manufacturers original finish and protect against stone chips, salt, damp and rust, as well as deaden sounds and vibrations. It is recoatable with most paint systems.

PHYSICAL PROPERTIES

Density at 20°C (g/cc)	1,00 - 1,06
Grinding Fineness (µ)	
Supply viscosity at 20°C	60 - 65 KU
%Solids content (weight / volume)	47,0 ± 2 %
V.O.C. (g/l)	549 (Grey 7470); 550 (Black 9005); 551 (White 9110); (Ready to use) (2004/42/CE) IIB (E) (840)
Type of product	Rubber
Colour	Black 9005, Grey 7470, White 9110

SURFACE PREPARATION

The treated surfaces must be dry, free from grease and rust. In order to achieve a better adhesion of the product, get rid of flaking paint, dirt or rust.

APPLICATION INSTRUCTIONS

- Shake before use.
- Suction antistonechip spray gun. Pressure: 3-6 bar.
- Apply one crossed coat.



One crossed coat
300 my



20°C/60'
60°C/30'



FEATURES OF DRY FILM

Theoretical yield (m ² /l)	1,6 (300 my)
Gloss 60°-60°	Satin
Second layer	

STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 25°C recommended. Can life: **2 years** from manufacturing in date its original unopened container. Consult our Technical Department once date has expired.