



SAFETY DATA SHEET

FARGLO FLUORESCENT PAINT YELLOW

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FARGLO FLUORESCENT PAINT YELLOW

Product number FUYEL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC 9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Supplier Axalta Coating Systems Huthwaite UK Ltd
Blackwell Road
Huthwaite
Nottinghamshire
United Kingdom
NG17 2RL
Tel: +44 (0)1623 510585

Contact person info-huthwaite@axaltacs.com

1.4. Emergency telephone number

Emergency telephone United Kingdom: 01623 528938 (Mon-Thu 0700 - 1600 hrs, Fri 0700 - 1245 hrs).

National emergency telephone number Republic of Ireland: National Poison Information Centre (Ireland) Tel: 01 809 2566 (8am to 10pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H335, H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

FARGLO FLUORESCENT PAINT YELLOW

| | |
|---------------------------------|--|
| Precautionary statements | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |
|---------------------------------|--|

Contains HYDROCARBONS, C9, AROMATICS

Other information

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|------------------------------------|--|
| HYDROCARBONS, C9, AROMATICS | 30-60% |
| CAS number: 64742-95-6 | EC number: 918-668-5 |
| | REACH registration number: 01-2119455851-35-0000 |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | Xn; R65. Xi; R37. N; R51/53. R10, R67 |
| STOT SE 3 - H335, H336 | |
| Asp. Tox. 1 - H304 | |
| Aquatic Chronic 2 - H411 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| General information | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues. |
| Inhalation | Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues. |
| Ingestion | Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. |
| Skin contact | Immediately remove contaminated clothing. Rinse immediately with plenty of water. |
| Eye contact | Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. |

4.2. Most important symptoms and effects, both acute and delayed

General information No data available on the mixture itself.

FARGLO FLUORESCENT PAINT YELLOW

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

For non-emergency personnel Keep unnecessary and unprotected personnel away from the area.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from oxidising materials, heat and flames.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

FARGLO FLUORESCENT PAINT YELLOW

8.1. Control parameters

Ingredient comments

WEL = Workplace Exposure Limits

HYDROCARBONS, C9, AROMATICS (CAS: 64742-95-6)

DNEL

Workers - Dermal; Long term systemic effects: 25 mg/kg bw/day
 Workers - Oral; Long term systemic effects: 150 mg/m³
 Consumer - Dermal; Long term systemic effects: 11 mg/kg bw/day
 Consumer - Inhalation; Long term : 32 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Use protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber; thickness 0.35mm minimum. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Store in a demarcated banded area to prevent release to drains and/or watercourses. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Yellow.

FARGLO FLUORESCENT PAINT YELLOW

| | |
|---|---|
| Odour | Characteristic. |
| Initial boiling point and range | 130°C |
| Flash point | 48°C |
| Upper/lower flammability or explosive limits | Lower flammable/explosive limit: 0.6% Upper flammable/explosive limit: 7.0% |
| Vapour pressure | Not available. |
| Relative density | 1.00 - 1.05 |
| Solubility(ies) | Immiscible with water. |
| Partition coefficient | No information available. |
| Viscosity | Kinematic viscosity > 20.5 mm ² /s. |

9.2. Other information

| | |
|----------------------------------|---|
| Other information | No additional information |
| Volatile organic compound | This product contains a maximum VOC content of 580 g/l. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|----------------------------------|
| Reactivity | Flammable/combustible materials. |
|-------------------|----------------------------------|

10.2. Chemical stability

| | |
|------------------|--|
| Stability | Stable at normal ambient temperatures. |
|------------------|--|

10.3. Possibility of hazardous reactions

| | |
|---|--|
| Possibility of hazardous reactions | Under normal conditions of storage and use, no hazardous reactions will occur. |
|---|--|

10.4. Conditions to avoid

| | |
|----------------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. |
|----------------------------|---|

10.5. Incompatible materials

| | |
|---------------------------|--|
| Materials to avoid | Avoid contact with the following materials: Acids. Oxidising agents. |
|---------------------------|--|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂). |
|---|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------------------|--|
| General information | Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. |
| Inhalation | Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. |
| Ingestion | Gastrointestinal symptoms, including upset stomach. Pneumonia may be the result if vomited material containing solvents reaches the lungs. |

FARGLO FLUORESCENT PAINT YELLOW

| | |
|---------------------|--|
| Skin contact | Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. Harmful in contact with skin. |
| Eye contact | Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. |

SECTION 12: Ecological information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity No data on the mixture itself.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

| | |
|-------------------------|------|
| UN No. (ADR/RID) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |
| UN No. (ADN) | 1263 |

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

FARGLO FLUORESCENT PAINT YELLOW

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

| | |
|-----------------------------|----|
| ADR/RID class | 3 |
| ADR/RID classification code | F1 |
| ADR/RID label | 3 |
| IMDG class | 3 |
| ICAO class/division | 3 |
| ADN class | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ICAO packing group | III |
| ADN packing group | III |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

| | |
|--|----------|
| EmS | F-E, S-E |
| ADR transport category | 3 |
| Emergency Action Code | •3Y |
| Hazard Identification Number (ADR/RID) | 30 |
| Tunnel restriction code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UFI UFI: 93PQ-G2YM-H007-2QY1

FARGLO FLUORESCENT PAINT YELLOW

| | |
|-----------------------|--|
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance | Workplace Exposure Limits EH40. 2018 Code of Practice for the Chemical Agents Regulations (HSA Ireland) |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|---|--|
| Abbreviations and acronyms used in the safety data sheet | WEL: Workplace Exposure Limit. ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. DMEL: Derived Minimal Effect Level. DNEL: Derived No Effect Level. OELV: Occupational Exposure Limit Value. PNEC: Predicted No Effect Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. |
| Revision date | 01/03/2019 |
| Revision | 6 |
| Supersedes date | 28/01/2016 |
| SDS number | 30576 |
| Risk phrases in full | R10 Flammable. R37 Irritating to respiratory system. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness. |
| Hazard statements in full | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. |

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.