| 23.06.2020 | Kit Components | |
|--------------|--|--|
| Product code | Description | |
| M000054 | Motip Reparaturbox Polyesterharz + Härter | |
| M000154 | 2 0.3 0000111122 1 22111 001 | |
| 426445 | | |
| 426452 | | |

Components:

| 000075 | Motip Hardener |
|--------|----------------------------|
| 000054 | Motip special Reparaturbox |



Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Motip Hardener
- · Article number: 000075, 000077alt, 000078, 000079, 000153, 496718alt, 496701alt, 894923alt, 894930alt
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI GmbH

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49/6266/75-0

msds@de.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Org. Perox. E H242 Heating may cause a fire.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

· Hazard pictograms

(Contd. of page 1)







GHS02

2 GHS07 GHS0

· Signal word Warning

· Hazard-determining components of labelling:

dibenzoyl peroxide

· Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with regional regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|---|---------|
| CAS: 94-36-0 EINECS: 202-327-6 Index number: 617-008-00-0 Reg.nr.: 01-2119511472-50 | dibenzoyl peroxide Org. Perox. B, H241 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10) Eye Irrit. 2, H319; Skin Sens. 1, H317 | 25-<50% |
| CAS: 131-11-3 EINECS: 205-011-6 Reg.nr.: 01-2119437229-36 | dimethyl phthalate substance with a Community workplace exposure limit | 25-<50% |
| CAS: 107-21-1 EINECS: 203-473-3 Index number: 603-027-00-1 | ethanediol Acute Tox. 4, H302 | 5-<10% |
| CAS: 67762-90-7 | fumed silica • Eye Irrit. 2, H319; STOT SE 3, H335 | 5-<10% |

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters ·
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 5.2
- \cdot 7.3 Specific end use(s) No further relevant information available.

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

94-36-0 dibenzoyl peroxide

WEL Long-term value: 5 mg/m³

131-11-3 dimethyl phthalate

WEL Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

107-21-1 ethanediol

WEL Short-term value: 104** mg/m³, 40** ppm

Long-term value: 10* 52** mg/m³, 20** ppm

Sk *particulate **vapour

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye protection:



Tightly sealed goggles

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

(Contd. of page 4)

| 9.1 Information on basic physical and c | hemical properties |
|---|---|
| General Information | • • |
| Appearance: | |
| Form: | Pasty |
| Colour: | Light red |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not applicable. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | : 197 °C (386.6 °F) |
| Flash point: | 111 °C (231.8 °F) |
| Flammability (solid, gas): | May cause fire. |
| Ignition temperature: | 410 °C (770 °F) |
| Decomposition temperature: | Not determined. |
| Explosive properties: | Product does not present an explosion hazard. |
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Vapour pressure at 20 °C (68 °F): | 1 hPa (0.8 mm Hg) |
| Density at 20 °C (68 °F): | $1.2 \ g/cm^3 (10 \ lbs/gal)$ |
| Relative density | Not determined. |
| Vapour density | Not applicable. |
| Evaporation rate | Not applicable. |
| Solubility in / Miscibility with | |
| water: | Fully miscible. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| Solvent content: | |
| Organic solvents: | 9.0 % |
| Water: | 11.0 % |
| VOC (EC) | % |
| | |
| Solids content: | 73.0 % |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- $\cdot \textbf{10.5 Incompatible materials:} \ \textit{No further relevant information available}.$

(Contd. on page 6)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| • | European | waste | catal | logue |
|---|----------|-------|-------|-------|
|---|----------|-------|-------|-------|

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 02 plastic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

(Contd. of page 6)

| SECTION 14: Transport informa | mon — |
|---|---|
| 4.1 UN-Number DR, IMDG, IATA | UN3108 |
| 4.2 UN proper shipping name DR | 3108 ORGANIC PEROXIDE TYPE E, SOLID, ENVIRONMENTALLY HAZARDOUS |
| MDG, IATA | ORGANIC PEROXIDE TYPE E, SOLID |
| 4.3 Transport hazard class(es) | |
| Class | 5.2 (P1) Organic peroxides. |
| abel | 5.2 (11) organic peroxides. |
| Class Label | 5.2 Organic peroxides. 5.2 |
| 4.4 Packing group MDG, IATA | II |
| 4.5 Environmental hazards: Aarine pollutant: pecial marking (ADR): | Yes Symbol (fish and tree) |
| 4.6 Special precautions for user towage Category towage Code egregation Code | Warning: Organic peroxides. D SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis. |
| 4.7 Transport in bulk according to Ann Iarpol and the IBC Code | nex II of Not applicable. |
| ransport/Additional information: | |
| DR imited quantities (LQ) Excepted quantities (EQ) | 500 g Code: E0 Not permitted as Excepted Quantity |
| N ''Model Regulation'': | UN 3108 ORGANIC PEROXIDE TYPE E, SOLID, 5.2, ENVIRONMENTALLY HAZARDOUS |

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip Hardener

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - oral – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

GF



Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Motip special Reparaturbox
- · Article number: 000054, 000154, 496657, 496664, 497197alt, M600054alt
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI GmbH

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

D-7-1033 Haysmershein

Tel.: +49/6266/75-0 msds@de.motipdupli.com

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

styrene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves / eye protection.

P281 Use personal protective equipment as required.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents / container in accordance with regional regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|-------------------------------|--|---------------|
| CAS: 100-42-5 | styrene | 25-<50% |
| EINECS: 202-851-5 | ⓑ Flam. Liq. 3, H226 | |
| Index number: 601-026-00-0 | & Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 | |
| Reg.nr.: 01-2119457861-32-xxx | x 🔥 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; | |
| | STOT SE 3, H335 | |
| | Aquatic Chronic 3, H412 | |
| CAS: 67-56-1 | methanol | ≤ 0.5% |
| EINECS: 200-659-6 | ♠ Flam. Liq. 2, H225 | |
| Index number: 603-001-00-X | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, | |
| Reg.nr.: 01-2119433307-44 | H331 | |
| | ♦ STOT SE 1, H370 | |

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

(Contd. on page 3)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters ·
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

(Contd. on page 4)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm

Long-term value: 266 mg/m³, 200 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Protection of hands:



Protective gloves

· Material of gloves

Fluorocarbon rubber (Viton)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length (Contd. on page 5)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 4)

of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye protection:



Tightly sealed goggles

| SECTION 9: Physical and chemic | |
|---|---|
| 9.1 Information on basic physical and ch General Information | iemicai properties |
| · Appearance: | |
| Form: | Fluid |
| Colour: | Amber coloured |
| · Odour: | Characteristic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | |
| Flash point: | 31 °C (87.8 °F) |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 480 °C (896 °F) |
| Decomposition temperature: | Not determined. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 8.9 Vol % |
| Vapour pressure at 20 °C (68 °F): | 6 hPa (4.5 mm Hg) |
| Density at 20 °C (68 °F): | $1.1 \ g/cm^3 (9.2 \ lbs/gal)$ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic at 20 °C (68 °F): | 90 s (DIN 53211/4) |
| · Solvent content: | |
| Organic solvents: | 37.1 % |
| VOC (EC) | |
| | 411.3 g/l |
| · VOC-EU% | 37.05 % |
| · Solids content: | 63.6 % |

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

100-42-5 styrene

| Oral | LD50 | 5000 mg/kg (rat) |
|------------|---------|------------------------------|
| Dermal | LD50 | >2000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50/4h | 11.8 mg/l (rat) |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 7)

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 99 wastes not otherwise specified

15 01 04 metallic packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| CECTION | 11.7 | P-1 01 - 0 0 - 0 0 | | C | 4 |
|------------------|------|--------------------|--------|--------------|----------|
| SECTION 1 | | | ri ini | COMMITTALE I | 11.0111. |
| 02021011 | | I wild po | , | 0.1.1.000 | |

· 14.1 UN-Number

· ADR, IMDG, IATA UN3269

· 14.2 UN proper shipping name

· ADR
3269 POLYESTER RESIN KIT
· IMDG
POLYESTER RESIN KIT
POLYESTER RESIN KIT mixture

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 3 (FT3) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· IMDG not regulated

· IATA III

· 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Warning: Flammable liquids.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 69
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eve irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to the hearing organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - oral - Category 3

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.06.2020 Version number 6 Revision: 11.07.2019

Trade name: Motip special Reparaturbox

(Contd. of page 8)

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.