

URKIPT Dye for Synthetic Materials



DESCRIPTION

Dye for reparation of bumpers, spoilers and any plastic surface of the car, such as plastic interior linings, rubber surfaces, cloth, plastic sliding roofs, etc.

COLORS

URKIPT	7493	9005
--------	------	------

SURFACE PREPARATION

Surfaces must be totally clean. Moisten the sponge with water and clean the surface to be restored with the rough part.

USE

Shake well before use.

Drain the sponge well and with the soft part, apply the dye evenly on the surface to be treated. For repainting, sanding, degreasing and pre-drying.

DRY FILM CHARACTERISTIC

Used for restoring old and damaged surfaces giving them a totally renewed look.

The appearance after repair is semi-gloss.

The dye is sensitive to moisture.

SAFETY INSTRUCTIONS 

The use of appropriate personal protective equipment is recommended during application, to prevent the irritation of the respiratory tract, skin and eyes. For professional use only.

STORAGE 

Keep in a tightly covered container, in a dry and ventilated place, avoiding direct exposure to sunlight. Temperature above 5°C is recommended, between 15 and 30°C optimal.

VOC 

The VOC content of URKIPT is a maximum of 840 g/l in compliance with European regulation 2004/42/EC IIB(E) (840) <840 g/l.

The information contained in this Technical Specification Sheet is based on the knowledge and experience of the BESA technical department, and with it it's intended to advice and inform, being the responsibility of the user to take the necessary measures to guarantee the intended purpose of the product. **FOR PROFESSIONAL USE ONLY.**
