

PINTURA DE PISCINAS AL CLOROCAUCHO PRESTIGE



Product Description

Paint of swimming pools and of maximum quality based on chlororubber resins and highly colour fast pigments



Technical Characteristics

Colour	Sky blue and white
Appearance	Satin
Touch-dry	30-60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	After 24 hours
Yield	6-8 m ² /l, per coat, depending on the state and type of surface
Thinner	DILUYENTE CLOROCAUCHOS 300
Storage	Excellent up to 1 year in original container, under normal temperature and humidity conditions.

Properties

Easy to apply
Finish hard-wearing, resistant and hard
Anti-algae effect, reduces their adherence onto the paintwork.
The great chemical stability of its composition means that it resists the constant action of water and of its disinfection and conservation treatments.

Applications

Suitable for protection and decoration de on swimming pools with cement mortar and other derivative surfaces.

Method of Use

Apply well ventilated and in thin, even, well-spread coats
A round brush and airless spray gun: as it comes in the pot or thinned with DILUYENTE CLOROCAUCHOS 300
Stir the contents of the pot well

Preparation of surfaces

On unpainted surfaces: Sandpaper, clean, brush, eliminate dust, grease, oil, nitre, incrustations, mould and other items that could affect anchoring and preferably leave rough to improve adherence
On with old paintwork surfaces: Remove damaged paintwork and proceed as for unpainted surfaces
Apply the following preparations:
On dry, set cement mortar and other derivatives. surfaces: Apply the same product diluted with rubber paint 300 solvent as preparation
On steel and iron apply MINIOBARP CLOROCAUCHO
On galvanised and light metals apply <?DENOMINACION>
Apply then at least two coats of the product

Recommendations before application

Do not apply in bright sunlight or in the presence of dew
Once the product is applied, leave for a week before filling the pool.
New pool: once built allow a month to pass before painting.

Other data

Packaging 0.75L, 4L, 15L

Remarks

MINIOBARP RUBBER PANT and WASH PRIMER-93 are products from the Industrial Conservation Product Line.
Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 07-11-2013 This sheet replaces all previous versions.