

SELLAFOND AL AGUA

Product Description Sealant for fixing soft, absorbent undercoats with alkalinity, etc. based on special acrylic resins.



Technical Characteristics

Colour	Colourless
Appearance	Semi-gloss, depending on the structure and absorption of the surface
Touch-dry	1/2-1 hour, depending on the absorption of the undercoat and ambient conditions
Repainting	2-4 hours (topcoat of another product, 6 hours).
Yield	6-10 m ² /l, per coat, depending on the state and type of surface
Thinner	Water
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

Properties

- Easy to apply
- Penetrating
- Filling power
- High sealing power
- Very permeable to the inner moisture of the surface
- Regulates the degree of absorption of the undercoat.
- Resistant to the alkalinity of surfaces
- Enhances adherence of finishing coats

Applications

Suitable for preparation of indoor surfaces, plastered surfaces and cement mortar..., especially designed for soft and crumbling surfaces, provides filling to the undercoat, strength and hardness.
Suitable for finish on brickwork façades, stone, concrete, mortars and rough decorative coatings.

Method of Use

- Stir the contents of the pot well
- Application at: Round brush and spray gun
- Sand if necessary

Preparation of surfaces

The surface should be clean, dry and free from grease, nitre, flaking and must be consistent.
Dilute with water to 300-400% (1 parts product at 3-4 parts water) depending on the structure and absorption of the surface.
Apply: 2 successive coats, wet on wet.
With each coat, apply until the surface is saturated (cover small areas so that the product is applied after having absorbed the previous coat).
Do not apply more than the surface can absorb.
The surface must be semi-matt.

Recommendations before application

Do not apply in temperatures below 5°C.

Other data

Packaging 0.75L, 4L, 15L

Remarks

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 11-12-2013 This sheet replaces all previous versions.