ANHIDREX ECOBARP AL AGUA

Product Description   Invisible for façades water repellent, special resins in aqueous medium based.

Technical Characteristics

Colour	Colourless
Appearance	Matt
Touch-dry	30-60 minutes, depending on the thickness applied and atmospheric conditions
Repainting	Successive coats, wet on wet
Yield	1-4 m² / l, coat depending on the structure and absorption of the undercoat
Thinner	No need to dilute. Ready to use
Storage	Excellent for up to 1 year/s, unopened, in original packaging, at normal temperature and humidity. Store in places protected against frost.

Properties

Easy to apply
Penetrating
Very permeable to the inner moisture of the surface
Avoids efflorescence and nitre
Resistant to the alkalinity of surfaces
Waterproofing on roofs, removes dirt deposits and enhances cleaning

Applications

Suitable for waterproofing of brickwork façades, stone, concrete, mortars and roofing..., without modifying decorative look.

Method of Use

Stir the contents of the pot well
Application at: Round brush and spray gun

Preparation of surfaces

The surface must be clean and dry and free from grease, nitre, old paint and must be consistent, free from loose, crumbling or flaking particles.
Apply: 2 successive coats, wet on wet.
With each coat, apply until the surface is saturated (cover small areas so that the product is applied after having absorbed the previous coat).

Recommendations before application

Do not apply in temperatures below 5ºC.

Other data

Packaging	0.75L, 4L and 15L

Remarks

Oficinas centrales / Headquarters / Siège social
San Fernando, 116. D.P. 26300 Nájera. La Rioja. Spain
Tel. (34) 941 410 000 / Fax (34) 941 410 111 / www.barpimo.com

Shake contents of containers before use.
For toxicological standards, consult FICHA DE SEGURIDAD.
Do not store opened or started containers.
Apply with good air renewal.

Oficinas centrales / Headquarters / Siège social
San Fernando, 116. D.P. 26300 Nájera. La Rioja. Spain
Tel. (34) 941 410 000 / Fax (34) 941 410 111 / www.barpimo.com