

PATINA LIJABLE



Product Description

Properties

Solvent-based patina.

Gives the wood a distressed, rustic look.

Easy to apply

Quick sanding

This range of products includes a series of basic colours which can be mixed together to create others.

Recommended use

Used as ready to use dye

Product specially developed to give wood an aged appearance and to strip mouldings, angles and grooves in the piece of furniture.

Certificados

[Certificado.de.Producto.Simbolo.de.Calidad.AIDIMA](#)



Technical Characteristics

	Norma	Value
Density (Kg/L)		Depending on colour
Reference		Depending on colour
System		Solvent
Appearance		Rustic
Drying		Very fast

Application Characteristics

Application System	Aerographic
Application on	Polyurethane primers (Fondipol) or Polyacrylic perfectly sanded and dust removed
Repainted	After 1 hours
Cleanliness	Steel wool

Remarks re application process

Sand the undercoat just before applying the dye to avoid adherence problems

Once the patina is dry, remove the excess with steel wool

Physical Chemical Resistance

	Norma	Value
Solidity to light		High (indoors)
Solidity to varnishing over		Good resistance to over-varnishing with nitro, PU and acid-based varnishes.
		Over-varnishing with UV and polyester varnishes not recommended.

Remarks

Shake contents of containers before use.

For toxicological standards, consult FICHA DE SEGURIDAD.

Do not store opened or started containers.

Maximum stability of the product is less than 12 months at 20°C.

This sheet has been created with informational purposes only and does not replace expert advice. The information provided reflects our current knowledge and have been obtained from our own experience, but under no circumstance do they entail any warranty whatsoever from our part. For this reason, we cannot accept any undesired consequence deriving from its use. 16-02-2012 This sheet replaces all previous versions.

