

BODY 600 ECO PAINT REMOVER SPRAY

Technical Data Sheet No 832

BODY
Remover Remover Faint support
TRANSPORT
Satoree

VOC compliant with the	
regulations	
regulations	

Easy to use

Excellent results

ECO friendly for mulation

Fast Action

Does not rust the surface

General Technical Description

A transparent ECO Paint Remover suitable for the removal of paint, clear coats and latex material from all metal and plastic surfaces. Also suitable for cleaning of paint tools (e.g. spray guns, spatulas etc).

Surface

Suitable for the removal of paint, clear coats and latex materials from all metal and plastic surfaces.

Pretreatment / Cleaning of substrate

Product Application: »» Spray one to two coats till the area needed to be cleaned is all covered with the paint remover foam. Allow the product to work for about 15 min. Use a spatula and lightly scrape off the residues of paint remained. In case of strong paint residues re-apply the product on the surface till all the old paint is removed.



Flash Point: -97°C

> **Specific Gravity:** 0.86 g/cm³

Solid Content (No thinner): 2,5% Weight

VOC (2004/42/EC)

This is an aerosol product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 830g/L. 2004/42/IIB(e)(840)830

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to

update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Theoretical Coverage:

Cleaning of equipment:

Remarks:

Always try to use the product in accordance with the specifications provided.
It can be used by countries that do not adopt the VOC legislation as well.
Do not overspray right away.
Allow for the first coat to activate the paint removing procedure and then reapply if necessary.
Surface / tools can be washed / cleaned with water after use.

Shelf life:

• Up to 36 months unused spray. • +5 to +25 °C



2-3 coats approximately

Shake well before

usina

HB BODY S.A. Auto Refinishing Products, Greece www.hbbody.com

Issue 3 / 2015, September 2015