

# Section 1. Product and Company Identification.

**1.1 Model Number**; CP400LI v1

**1.2 Description;** Cordless Impact Wrench 18V 3Ah Li-ion 1/2"Sq Drive

Battery: 18 Volts. 3 Ah. 68 grams.

#### 1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 29/03/2018

### Section 2. Hazards Identification.

Battery is hermetically sealed and does not present a hazard under normal conditions of use. Inappropriate handling and / or use can cause electrolyte to leak.

**Ingestion:** Contents of an open battery can cause chemical burns of mouth, oesophagus, and gastrointestinal

tract.

**Inhalation:** Contents of an open battery can cause respiratory irritation.

**Skin Contact:** Contents of an open battery can cause skin irritation. **Eye Contact:** Contents of an open battery can cause irritation.



# Section 3. Substances.

		Classification		
3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Weight	Hazard Class & Category Code	Hazard Statements <sup>1</sup>
Cobalt lithium manganese nickel oxide	182442-95-1	20 – 30 %	-	-
Graphite	7782-42-5	15 – 20 %	-	-
Iron	7439-89-6	15 – 20 %	-	-
Aluminium foil	7429-90-5	5 – 10 %	Flam. Sol. 1	H228
			Water-react. 2	H261
Copper foil	7440-50-8	5 – 10 %	-	-
Lithium hexafluorophosphate	21324-40-3	2-3%	-	-
Ethylene carbonate	96-49-1	2-3%	-	-
Dimethyl carbonate	616-38-6	2-3%	Flam. Liq. 2	H225
Ethyl methyl carbonate	623-53-0	2-3%	-	-
Diethyl carbonate	105-58-8	2-3%	-	-

<sup>&</sup>lt;sup>1</sup>For full text of Phrases and Statements, see Section 16.



### Section 4. First Aid Measures.

Lithium Batteries do not pose a risk to eyes or skin under normal circumstances. In the case of contact with internal substances;

#### 4.1 Description of first aid measures

#### **Inhalation**

If breathing difficulties develop, remove the person to fresh air.

Loosen close fitting clothing.

Ensure that person is warm.

If mouth to mouth resuscitation is necessary, the person conducting this must takes steps to reduce the risk of contamination from toxic / corrosive substances that may be present.

#### **Skin Contact**

Remove contaminated clothing.

Flush affected area(s) with copious amounts of water for at least 15 minutes.

Get medical attention.

#### **Eye Contact**

Irrigate eyes with water for at least 15 minutes while raising eyelid(s).

Get medical attention.

#### Ingestion

If swallowed, do not induce vomiting. Give large amounts of water but do not do this if casualty is unconscious.

#### Protection of First Aiders:

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

# **4.2.** Most important symptoms and effects, both acute and delayed No data available.

**4.3.** Indication of any immediate medical attention and special treatment needed No data available.



### **Section 5. Fire Fighting Measures.**

#### Recommended practice;

Always ensure that Personal Protection Equipment (PPE) is used.

If a battery becomes hot, immediately remove it from flammable materials and place on a non-combustible surface. If possible, place a disintegrating device outdoors and allow it to burn out.

Fire condition; NB; ensure that electrical devices are turned off. Prevent electric shock risk.

If any batteries are burning, water may not extinguish them, but will cool the adjacent batteries and control the spread of fire.

#### 5.1. Extinguishing media

#### **Extinguishers**;

Only use Graphite based CO<sub>2</sub> (Carbon dioxide), Dry Powder or Foam.

Copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.

If possible, use a **LITH-X (powdered graphite)** extinguisher on small fires. This material acts as a smothering agent. A **sodium chloride powder** extinguisher **IS NOT** suitable for use on Lithium Batteries.

It may not be possible to extinguish burning lithium batteries. Burning batteries will burn themselves out. <u>Do not use water</u> with **LITH-X (powdered graphite)**.

• If a LITH-X (powdered graphite) extinguisher is not available;

Use copious amounts of water in a fine spray to swamp a fire.

Continue to use copious amounts of water until the fire is extinguished and the batteries are cooled.

NB: Lithium reacts with water to form Hydrogen. The fire will not be extinguished immediately.

Be aware of the increased risk of explosion.

NB; fire-fighting water runoff may be corrosive / toxic and may cause adverse environmental impact.

#### **5.2.** Special hazards arising from the substance or mixture

Hazard characteristics; thermal decomposition can lead to the release of toxic fumes.

Hazardous combustion products; carbon dioxide, carbon monoxide, lithium oxide fumes.

#### **5.3.** Advice for fire-fighters

Fragments may be ejected from a fire.

Fire Fighters should wear self-contained breathing apparatus and appropriate Personal Protective Equipment.



### Section 6. Accidental Release Measures.

**6.1.** Personal precautions, protective equipment and emergency procedures In the event of battery rupture and leakage,

- ventilate the area.
- wear appropriate protective clothing (see Section 8) to prevent eye and skin contact and to prevent inhalation of vapours or fumes.
- remove sources of ignition.

#### 6.2. Environmental precautions

No data available.

### 6.3. Methods and material for containment and cleaning up

Absorb released materials with inert absorbent (dry sand or soil).

Collect released materials into sealed plastic bag or container.

Prevent material from contaminating soil or entering sewers or waterways.

Do not dispose of released materials with domestic waste

Do not allow product to enter ground water, water course or sewerage system.

Dispose of released materials in accordance with local authority regulations.

#### 6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

# Section 7. Handling and Storage.

#### 7.1. Precautions for safe handling

Never dismantle or modify a battery.

Do not short circuit a battery. A short circuit causes heating and can lead to ignition of surrounding materials.

Physical contact with a short-circuited battery can cause skin burn.

When charging the battery, use dedicated chargers and follow the specified conditions.

Improperly charging a battery may cause the battery to combust.

Lithium batteries for transport by air in a state of charge must have no more than 30% charge of their rated capacity.

#### **7.2.** Conditions for safe storage, including any incompatibilities

Prevent contact with conductive materials.

Do not allow contact with water.

Store in original container. Keep container tightly closed.

Store in a dry, cool place.

Store at 20 °C (68°F); room temperature

Store away from ignition sources, heat, and incompatible materials.

#### **7.3.** Specific end use(s)

Intended for use as the battery for the Model Number identified in 1.1 with Description stated in 1.2



# Section 8. Exposure Controls/Personal Protection.

#### **8.1.** Control parameters

In the event of battery rupture and leakage:

Ventilate the area.

Remove sources of ignition.

#### 8.2. Exposure controls

The use of Personal Protective Equipment (PPE) is not necessary under conditions of normal use.

If handling a leaking or ruptured battery, ensure that the following Personal Protective Equipment (PPE) is used.

#### **Eye/Face Protection**

Chemical grade full face shield

#### **Skin Protection**

Acid resistant, natural rubber or neoprene gloves.

Protective rubber apron

Appropriate Personal Protection with long sleeves and long trousers.

#### **Respiratory Protection**

Acid gas filter mask or self-contained breathing apparatus.

# Section 9. Physical and Chemical Properties.

#### 9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance: Black plastic shell

(b) Odour: Not relevant to battery as supplied.(c) Odour threshold; Not relevant to battery as supplied.

(d) pH: No data available.
(e) Melting point/freezing point; Not relevant.
(f) Initial boiling point and boiling range; Not relevant.
(g) Flash point; No data available.

(h) Evaporation rate; Not relevant to battery as supplied.

(i) Flammability (solid, gas);
No data available.
(j) Upper/lower flammability or explosive limits;
No data available.
No data available.
Not relevant.
(l) Vapour density;
Not relevant.
(m) Relative density;
Not relevant.

(n) Solubility(ies); Battery insoluble in water.

(o) Partition coefficient: n-octanol/water;
(p) Auto-ignition temperature;
(q) Decomposition temperature;
(r) Viscosity;
(s) Explosive properties;
(t) Oxidising properties.
Not relevant.
No data available.
No data available.
No data available.

**9.2** Other information None



# Section 10. Stability and Reactivity.

**10.1.** Reactivity No data available.

**10.2.** Chemical stability Stable under normal conditions.

**10.3.** Possibility of hazardous reactions No data available.

**10.4.** Conditions to avoid Mechanical shock.

Vibrations during transport are not detrimental to condition.

Do not dismantle, crush or install with incorrect polarity.

Prevent mechanical / electrical misuse.

**10.5.** Incompatible materials No data available.

**10.6.** Hazardous decomposition products Metal oxides, CO, CO<sub>2</sub>.

# Section 11. Toxicological Information.

11.1. Information on toxicological effects

#### Potential health risks;

Eye; Contact with battery contents may cause severe irritation and burns. Eye damage is possible.

**Skin**; Contact with battery contents may cause severe irritation and burns.

Absorption through the skin will cause localized inflammation.

**Ingestion**; may cause severe and permanent damage to the digestive tract. May cause circulatory system failure. Contents of an open battery can cause serious chemical burns to the mouth, oesophagus and gastrointestinal tract. **Inhalation**; Inhalation of vapours or fumes released due to heat or leaking batteries may cause respiratory irritation. Irritation may lead to chemical pneumonitis.

Inhalation can produce chronic productive cough and shortness of breath.

# **Section 12. Ecological Information.**

When properly used and disposed of correctly, the battery does not present environmental hazard.

Do not release internal components into water ways, wastewater or ground water.

# Section 13. Disposal Considerations.

Disposal of the battery must be in accordance with local authority regulation requirements for hazardous waste treatment and hazardous waste transportation.

The battery should be completely discharged prior to disposal and the terminals taped or capped to prevent short circuit.

Do not dispose of batteries at landfill sites.

Do not incinerate batteries.



# **Section 14. Transport Information.**

### ADR. International Carriage of Dangerous Goods by Road.

**14.1.** UN number UN 3481

**14.2.** Name and Description Lithium ion batteries contained in equipment

**14.3.** Transport hazard class(es) **9. 14.4.** Packing group

**14.5.** Environmental hazards Does not present an environmental hazard.

**14.6.** Special precautions for user No special precautions necessary.

#### IATA. International Air Transport Association.

**14.1.** UN number UN 3481

**14.2.** UN Proper Shipping Name/Description Lithium ion batteries contained in equipment

**14.3.** Transport hazard class(es) **9. 14.4.** Packing group

**14.5.** Environmental hazards Does not present an environmental hazard.

**14.6.** Special precautions for user No special precautions necessary.

### IMDG. International Maritime Dangerous Goods.

**14.1.** UN number UN 3481

**14.2.** UN proper shipping name Lithium ion batteries contained in equipment

**14.3.** Transport hazard class(es) Class or Division

**14.4.** Packing group

**14.5.** Environmental hazards Does not present an environmental hazard.

**14.6.** Special precautions for user No special precautions necessary.

**14.7.** Transport in bulk – Maritime only. Bulk transport is not applicable to this product



# Section 15. Regulatory Information.

**15.1.** Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

**15.2.** Chemical safety assessment No data available.

### Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	12/11/19	First issue.

End of Safety Data Sheet.