

## ANTI-RUST METAL PAINT

Nitromors Smooth Metal
Paint is for use on metal
doors, metal garden
furniture, metal gates and
railings, no primer is required. Excellent resistance
to UV and colour fading. For use on both ferrous and
non-ferrous metal substrates. The powerful
formulation will provide rust protection and salt
spray resistance.

## ANTI-RUST METAL PAINT Lang form rust systemion Sired to rust spolication

## **HOW TO USE**

- **1.** Ensure area to be painted is free from dust, flakes of rust, grime, greases, and oils etc. by abrading the surface where required and wipe with a cloth dampened with white spirit.
- 2. Allow to dry.
- 3. Shake the can for at least 2 minutes, repeat shaking at regular intervals during use.
- **4.** Apply sparingly from a distance of 15-25cm. Apply 2 to 3 light coats as necessary to achieve total and even coverage, leaving 15 minutes between each application.
- 5. Allow to dry for 24 hours to develop the maximum paint hardness.
- **6.** On completion of use, invert the can and depress the nozzle for a few seconds to prevent nozzle blockage.

Appearance ————————————————————————————————————		Coloured liquids with characteristic paint odours.
Specific Gravity		0.900 to 0.955  Medium Viscosity liquids.  10 to 25  Extremely flammable aerosol.
Viscosity		
Active Content % m/m		
Flammability		
Composition Data		Solvent based solutions of alkyd and acrylic resins containi xylene, acetone, pigments, driers, plasticisers and wetting agents dispersed in a liquefied propellant.
Product Code	Size	Barcode
		5010373143285





Danger - Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ fee protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if presentand easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local regulations. Repeated exposure may cause skin dryness or cracking. Contains Acetone.

CAUTION: Pressurised container may burst if heated. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only as directed.

