



RUST ARMOUR

Nitromors Rust Armour Protects surfaces from rust and corrosion whilst also providing an impermeable weather proof layer that displaces moisture. This unique formula is ideal for coating tools and garden equipment. Nitromors Rust Armour leaves a clear, flexible, armour coating that will prevent rust from appearing.




HOW TO USE

1. Clean the surface thoroughly with a wire brush to remove all loosely adhering and friable deposits.
2. Wash with a detergent solution to remove any grime or dirt, rinse and allow to dry.
3. Apply from a distance of 25 to 30cm and allow to dry.
4. When further coats are required, allow 20 minutes between applications.
5. After use, invert can and spray for a few seconds to clear nozzle.



■ Appearance	Clear liquid with characteristic paint odour.
■ Specific Gravity	0.950 +/- 0.015
■ Active Content % m/m	10 to 25
■ Viscosity	Low viscosity liquids
■ Flammability	Extremely flammable aerosol.
■ Composition Data	A solution of an alkyd resin, plasticizer, and a blend of anti-skinning and drying promoters in a mixture of aromatic and ketone solvents in butane/isobutane/propane propellants.

Product Code	Size	Barcode
NRS500	500ml	5010373142912



ENVIRONMENTAL PROTECTION & SAFETY PRECAUTIONS



Danger - Extremely flammable aerosol. Pressurised container: may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection. **IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Repeated exposure may cause skin dryness or cracking. Use only as directed. Contains Acetone, Xylene (Mixture of isomers).